

PowerLite[®] 680 for SMART Board[®] Interactive Whiteboards

XGA
Resolution
1024 x 768



Shown with optional wall mount (sold separately)

Ultra short-throw presentation display for interactive SMART Boards.

Compatible — specially designed to work with SMART Board M680 and 880 interactive whiteboards

Seamless integration — connect and control your display via the SMART Extended Control Panel (ECP)¹

Up to 3x Higher Color Brightness², and reliable performance — 3LCD, 3-chip technology

Bright display — 3,500 lumens color/white brightness³

Long-life lamp — lasts up to 10,000 hours in ECO Mode⁴

Incredible image quality — native XGA resolution (1024 x 768) and 4:3 format

Ultra short-throw presentation display — get a 77" image from less than 7" away with virtually no shadow interference

Manage your display and send announcements remotely — easy network connectivity; software included

Wireless support — display Chromebook[™], iOS[®], Android[™], Mac[®] and PC screens⁵

Versatile connectivity — 3x HDMI[®] supports multiple high-definition A/V devices, with MHL[®] support⁶



Specifications

Projection System 3LCD, 3-chip technology
Projection Method Front/rear/wall mount/table
Driving Method Poly-silicon TFT Active Matrix
Pixel Number 786,432 dots (1024 x 768) x 3
Color Brightness³ Color Light Output: 3,500 lumens
White Brightness³ White Light Output: 3,500 lumens
Aspect Ratio 4:3
Native Resolution 1024 x 768 (XGA)
Resize 640 x 480 (VGA); 800 x 600 (SVGA); 1152 x 864 (SXGA); 1280 x 800 (WXGA); 1280 x 960 (SXGA2); 1280 x 1024 (SXGA3); 1280 x 768 (WXGA 60-1); 1366 x 768 (WXGA 60-2); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1600 x 900 (WXGA++); 1600 x 1200 (UXGA)
Lamp Type 250 W UHE
Lamp Life⁴
 Up to 10,000 hours (ECO Mode)
 Up to 5,000 hours (Normal Mode)
Throw Ratio Range 0.32 – 0.43
Size (Projected Distance)
 55.4" – 92.7" (0.34 – 0.60 m)
Keystone Correction (Manual)
 Vertical: ±3 degrees
 Horizontal: ±3 degrees
Mac Connectivity Projector is Mac compatible via USB; DVI to HDMI or VGA adapter (not included); DP to HDMI or VGA adapter (not included)
Contrast Ratio Up to 14,000:1
Color Reproduction Up to 1.07 billion colors

Projection Lens


Type Digital zoom/Manual focus
F-number 1.6
Focal Length 3.7 mm
Zoom Ratio Digital zoom: 1.0 – 1.35

Other

Display Performance
 NTSC: 480 lines
 PAL: 576 lines (Depends on observation of the multi-burst pattern)
Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM
Speaker 16 W (mono)
Operating Temperature 41 ° to 104 °F (5 ° to 40 °C)
Power Supply Voltage 100 – 240 V ±10%, 50/60 Hz
Power Consumption
 373 W (Normal Mode)
 324 W (ECO Mode)
 2.2 W Standby (Communication On)
 0.23 W Standby (Communication Off)
Fan Noise
 35 dB (Normal Mode)
 30 dB (ECO Mode)
Security Kensington-style lock provision, padlock and security cable hole, Password-protect Function

Interfaces

Wireless LAN Port 802.11 (USB) b/g/n (Optional – module sold separately)
 Microphone: 1x
 RS-232c: 1x
 Video: 1x
 Audio in: 3x Mini Stereo
 USB (Type B): 1x
 USB (Type A Power): 1x
 Audio-out: 1x
 Monitor-out: 1x / Computer 2
 Computer: 2x
 Network: 1x RJ-45
 3x HDMI (1x MHL)



Dimensions (W x D x H)

Including Feet 14.5" x 15.8" x 7.4"
Excluding Feet 14.5" x 15.8" x 5.9"
Weight 12.6 lb

Remote Control

Features Source Search, HDMI/Video, LAN, Computer, USB, Power, Aspect, Color Mode, Volume, E-zoom, A/V Mute, Freeze, Menu, Page Up and Down, Home, Auto, Mouse Functions, User, Split Screen⁷
Operating Distance Front/rear: 19.7 ft (6 m)

Eco Features

RoHS compliant
 Recyclable product⁸
 Epson America, Inc. is a SmartWay[®] Transport Partner⁹

Support

Epson ConnectionSM
 Pre-sales support
 U.S. and Canada: 800-463-7766
 www.epson.com
Service Programs 2-year projector limited warranty, Epson Road Service program, PrivateLine[®] dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

PowerLite 680 projector for SMART, 15' power cord, projector remote control, batteries, user manual CD, projector software CDs, Quick Setup Sheet, Installation Guide, template sheet, projector feet

Ordering Information

| | |
|---|------------|
| PowerLite 680 for SMART | V11H746520 |
| Genuine Epson Lamp | V13H010L91 |
| Air Filter (ELPAF49) | V13H134449 |
| PowerLite Pilot™ 2 (ELPCB02) | V12H614020 |
| Active Speakers (ELPSP02) | V12H467020 |
| Wireless 802.11b/g/n LAN Unit (ELPAP10) | V12H731P02 |
| Epson DC-21 Document Camera (ELPDC21) | V12H758020 |
| 100" Whiteboard | V12H831000 |
| Ultra Short-throw Wall Mount (ELPMB46) | V12H777020 |
| Adapter for SMART UF55/65/70/75 series mounts | V12H870001 |



205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

1 Existing SMART Board M680 and 880 installations require the SMART Cable Adapter Kit, sold separately. | 2 Color brightness (color light output) in brightest mode, measured by a third-party lab in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. Top-selling Epson 3LCD projectors versus top-selling 1-chip DLP projectors based on PMA Research sales data for Dec. 2015 through Nov. 2016. | 3 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 4 Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | 5 For wireless functionality, including via the Epson iProjection™ App, the projector must be configured on a network, either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable a wireless connection. Not all Epson projectors are able to be networked. The Epson iProjection App does not support all files and formats. See www.epson.com for details. | 6 Includes one Mobile High-Definition Link[®] (MHL) HDMI port. | 7 Consult your user manual for input combinations. | 8 For convenient and reasonable recycling options, visit www.epson.com/recycle | 9 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Learn more about how our products can empower your institution. Visit us at www.epson.com/foreducation

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. PrivateLine is a registered trademark, Pilot is a trademark and Epson Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. Android and Chromebook are trademarks of Google Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2017 Epson America, Inc. Com-SS-Oct-13 CPD-52577 4/17

