

# EB-PU2116W 16,000-Lumen 3LCD Laser Projector with 4K Enhancement

## Ultra Bright

Color Brightness: 16,000 lumens<sup>1</sup>

White Brightness: 16,000 lumens<sup>1</sup>



Product shown with lens. Lens sold separately.

Projectors

Large Venue

## Premium large-venue laser projector with 4K enhancement<sup>2</sup>.

**Incredible color** — Epson<sup>®</sup> 3-chip 3LCD technology produces 16,000 lumens of equal white and color brightness<sup>1</sup> from a standard 120 V power source

**WUXGA with 4K Enhancement<sup>2</sup>** — accepts 4K content and delivers up to 4.6 million pixels on-screen for an incredibly crisp and vibrant image

**Long-lasting laser light source** — 20,000-hour virtually maintenance-free laser light source<sup>3</sup>

**Simplified installation** — 9 optional powered lenses (sold separately), including an ultra short-throw .35 throw lens with unique zero offset design, provide enhanced flexibility and convenience during installation

**Engineered for reliability** — hermetically sealed optical engine offers high dust resistance while filterless cabinet and liquid cooling system support easy, low-maintenance operation

**Outstanding image quality** — high native contrast ratio produces deep blacks; frame interpolation delivers realistic moving images; HDR support<sup>4</sup> and scene adaptive gamma correction for true-to-life images

**Fast installation** — built-in NFC functionality<sup>5</sup> to streamline multi-projector installations using the easy-to-use Epson Projector Configuration Tool (EPCT)<sup>6</sup> mobile app for Android™ and iOS<sup>®</sup>

**Optional attachable PixAlign™ camera** — provides access to powerful features, including projector stacking assist function<sup>7</sup>, tiling assist<sup>7</sup> for edge blends, color calibration<sup>8</sup> and screen matching<sup>8</sup>

**Simple Stacking function** — quickly stack two projectors using a remote controller instead of conventional setup with a PC and router; requires optional attachable PixAlign camera<sup>8</sup>



**Specifications**

**Projection System** High-aperture Epson 3LCD, 3-chip technology  
**Projection Method** Front/rear/ceiling mount  
**Driving Method** Poly-silicon TFT Active Matrix  
**Pixel Number** 2,304,000 dots (1920 x 1200) x 3  
**Signal Input** Maximum Display Resolution: 4096 x 2160 (resizing display); Display Resolution: 1920 x 1200 pixels  
**Native Resolution** WUXGA with 4K Enhancement<sup>2</sup> (1920 x 1200 x 2)  
**Resolution on Screen** WUXGA with 4K Enhancement<sup>2</sup>/4.6 million pixels  
**Aspect Ratio** Supports 4:3, 16:9, 16:10  
**Pixel Arrangement** Cross stripe  
**Color Brightness<sup>1</sup>** Color Light Output: 16,000 lumens  
**White Brightness<sup>1</sup>** White Light Output: 16,000 lumens  
**Contrast Ratio** 2,500,000:1 (Dynamic Contrast: On)  
**Brightness Uniformity (Typical)** 85%  
**Color Reproduction** Up to 1.07 billion colors  
**Lens Shift** Vertical: ±60%; horizontal: ±18%  
**Keystone Correction** Vertical: ±45 degrees; horizontal: ±30 degrees  
**Illumination Technology** Laser Diode

**Projection Lens (Standard)**  
 See website for information on optional lenses.  
**Standard Lens** ELPLM15 (sold separately)  
**Type** Powered shift/focus/zoom  
**F-Number** 2.0 – 2.1  
**Focal Length** 14.8 mm – 17.7 mm  
**Zoom Ratio** Optical zoom: 1.0 – 1.6  
**Throw Ratio Range** 1.57 – 2.56  
**Lens Shift** Vertical: ±60%; horizontal: ±18%

**Other Features**

**Operating Temperature** 32° to 122 °F (0° to 50 °C)  
**Power Supply Voltage** 100 – 120 V ± 10%, 50/60 Hz AC  
**Power Consumption**  
 1,118 W (Normal / Custom)  
 791 W (Quiet / Extended)  
 2.0 W Standby (Network Standby)  
 0.4 W Standby (Energy Saving)  
**Fan Noise** 38 dB (Normal Mode); 34 dB (ECO)  
**IP Rating** IP5X<sup>9</sup>  
**Security** Security cable hole, lens lock, Kensington<sup>®</sup> lock provision, wireless LAN unit lock

**Video I/O**

**Input Signal** Input Video Signal (HDMI<sup>®</sup>, DVI-D and HDBaseT<sup>™</sup> ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/4096 x 2160

**Interfaces**

HDMI x 1 (HDCP 2.3)  
 HDBaseT x 1  
 DVI-D x 1  
 VGA x 1  
 Variable audio out: Mini Stereo x 1  
 USB Type B x 1  
 USB Type A x 2 (5 V, 2.0 A)  
 USB Type A for Wireless LAN (optional)  
 Serial: RS-232C x 1 (9-pin)  
 Remote Mini Stereo  
 Network: RJ-45



**Dimensions / Weight**

**Including Feet (W x D x H)** 23.1" x 19.4" x 8.6"  
**Weight** 53.5 lb (24.3 kg)

**Remote Control**

**Features** Power; Source Search Selection; Lens Shift/Zoom/Focus; Test Pattern Selection; A/V Mute, Freeze, User ID, Auto Aspect, Color Mode, Number, Page Up and Down, E-Zoom, Volume, Help, Menu, Enter, ESC and Pointer Functions  
**Operating Angle**  
 Front: Right/Left: 60 to +60; Upper/Lower: +30 to 30 degrees  
 Rear: Right/Left: 30 to +30; Upper/Lower: +40 to +10 degrees  
**Operating Distance** 98 ft

**Eco Features**

RoHS compliant  
 Recyclable product<sup>10</sup>  
 Epson America, Inc. is a SmartWay<sup>®</sup> Transport Partner<sup>11</sup>

**Support**

**Epson Connection<sup>SM</sup>**  
 Pre-sales support: U.S. and Canada: 800-463-7766  
 Internet website: www.epson.com

**Service Programs**

The projector has a limited warranty of 3 years

**What's in the Box**

EB-PU2116W projector, power cable, remote control with two batteries, cable cover, user guide and warranty sheet

**Ordering Information**

|  |            |
|--|------------|
| Epson EB-PU2116W                           | V11HA64920 |
| Ultra Short-Throw Lens (ELPLX02S)          | V12H004X0B |
| Ultra Short-Throw Lens - White (ELPLX02WS) | V12H004Y0B |
| Short-Throw #1 Zoom Lens (ELPLU03S)        | V12H004UA3 |
| Short-Throw #2 Zoom Lens (ELPLU04)         | V12H004U04 |
| Wide-Throw #2 Zoom Lens (ELPLW06)          | V12H004W06 |
| Wide-Throw #3 Zoom Lens (ELPLW08)          | V12H004W08 |
| Middle-Throw #2 Zoom Lens (ELPLM15)        | V12H004M0F |
| Middle-Throw #3 Zoom Lens (ELPLM10)        | V12H004M0A |
| Middle-Throw #4 Zoom Lens (ELPLM11)        | V12H004M0B |
| Long-Throw Zoom Lens (ELPLL08)             | V12H004L08 |
| Rigging Frame (ELPMB59)                    | V12H996A01 |
| Wireless LAN Module (ELPAP11)              | V12H005A02 |
| Projector Ceiling Mount (ELPMB67)          | V12HA54010 |
| Suspension Adapter (ELPFP15)               | V12HA55010 |
| PixAlign Camera (ELPECO1)                  | V12HA46010 |

1 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 2 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | 3 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m<sup>3</sup> of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 HDR performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 5 NFC requires use of a device that includes NFC, and may require additional software. | 6 Internet connection required for download. Data usage fee may apply. | 7 Requires Epson external camera or built-in camera for each projector and the Epson Projector Professional Tool app. | 8 Using separate camera for each projector. | 9 IP5X-certified optical engine and Laser light source module in accordance with IEC standard 60529. | 10 For convenient and reasonable recycling options, visit www.epson.com/recycle | 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at [www.epson.com/forbusiness](http://www.epson.com/forbusiness)

**Better Products for a Better Future<sup>™</sup>**  
eco.epson.com



**Epson America, Inc.**  
3131 Katella Ave., Los Alamitos, CA 90720

**Epson Canada Limited**  
185 Renfrew Drive, Markham, Ontario L3R 6G3

[www.epson.com](http://www.epson.com)  
[www.epson.ca](http://www.epson.ca)

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PixAlign is a trademark of Epson America, Inc. and Epson Connection is a service mark of Epson America, Inc. Android is a trademark of Google LLC. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2022 Epson America, Inc. Com-SS-Oct-13 CPD-62052R1 3/22

