

# 1140 Series

## LED Heavy Duty Work Lighting

[ericson.com/1140](http://ericson.com/1140)

**NEW AND IMPROVED!**  
**NOW WITH 24,000 LUMENS**

- Outdoor and wet location rated
- Feed-thru connectivity option
- Low power utilization and consumption
- Lightweight, heavy duty and impact resistant material
- Fixture can be mounted horizontally overhead or vertically on the ground
- 50,000-hour lamp life
- Battery backup available with -EL part numbers



1140-25-LED



Vertical Light Stand



1140-25F-LED

	Part No.	Electrical Rating	Primary Cord Length (feet)	Secondary Cord Length (feet)	Primary Plug (NEMA)	Secondary Connector (NEMA)	Lumens	Color	Weight
Standard LED Lighting	1140-4-LED	120VAC 1.46A	5 ft.	None	5-15	None	23,900	5000K	20.7 lbs.
	1140-4F-LED	120VAC 12A	5 ft.	.5 ft.	5-15	5-15	23,900	5000K	21.5 lbs.
	1140-25-LED	120VAC 1.46A	25 ft.	None	5-15	None	23,900	5000K	22.3 lbs.
	1140-25F-LED	120VAC 12A	25 ft.	.5 ft.	5-15	5-15	23,900	5000K	24.1 lbs.
	1140-50-LED	120VAC 1.46A	50 ft.	None	5-15	None	23,900	5000K	24.4 lbs.
	1140-50F-LED	120VAC 12A	49.5 ft.	.5 ft.	5-15	5-15	23,900	5000K	27.4 lbs.
Emergency Egress Lighting	1140-4-LED-EL	120VAC 1.08A	5 ft.	None	5-15	None	16,800	5000K	24.4 lbs.
	1140-4F-LED-EL	120VAC 12A	5 ft.	.5 ft.	5-15	5-15	16,800	5000K	25.3 lbs.
	1140-25-LED-EL	120VAC 1.08A	25 ft.	None	5-15	None	16,800	5000K	26.1 lbs.
	1140-25F-LED-EL	120VAC 12A	25 ft.	.5 ft.	5-15	5-15	16,800	5000K	27.9 lbs.
	1140-50-LED-EL	120VAC 1.08A	50 ft.	None	5-15	None	16,800	5000K	28.1 lbs.
	1140-50F-LED-EL	120VAC 12A	49.5 ft.	.5 ft.	5-15	5-15	16,800	5000K	31.1 lbs.

Battery backed output is 10W 2300 lumens when running on battery power

Temporary Lighting

72



1.800.ERICSON  
1.800.374.2766

[ericson.com](http://ericson.com)  
[ericson.com/rfq](http://ericson.com/rfq)

