



1. AWG 12 & 14 MODELS ARE ETG AND cETL LISTED FILE 3132839CRT-002
2. STRINGLIGHT DESIGNED TO BE SUPPORTED AT EACH SOCKET.
3. TYPICAL DIMENSIONS SHOWN. SEE TABLE FOR SPECIFIC INFORMATION
25FT PRIMARY STANDARD ON ALL UNITS UNLESS STATED OTHERWISE.
4. MANUFACTURE AND TEST PER MP-022 & TEST RECORD 1003P
5. ELECTRICAL RATING: SEE TABLE.
6. DO NOT SUBMERGE. DO NOT USE IN STANDING WATER.
7. DROPS MOLDED FROM TPE ELASTOMER.
8. STRING APPROVED FOR CLASS I DIV 1&2 GROUPS C&D (100W MAX) AND CLASS II DIV 1&2
GROUPS F&G (60W MAX). APPROVED FOR BOTH AT 60W MAX. T-CODE T3C AT 100W.
9. MAX LED BULB WATTAGE 11W. MAX CFL WATTAGE IS 23W. MAX INCAND WATTAGE IS 100W
10. LABEL C8020650 NOT FURNISHED ON A UNIT WITH AN XP PLUG.

ERICSON MANUFACTURING COMPANY
1-800-ERICSON • www.ericson.com

DWG. TITLE		
2600 STRINGLIGHT 12/3 SEOW CABLE XP STRINGLIGHTS		
SCALE NTS	PROJ NO. --/--	SHEET 1 OF 2
DWG. UNIT NO.		REV
2600 STRINGLIGHT FAMILY		F