

1941-12-C1D2

TRANSFORMER XP CLASS 1 DIV 2, LOW VOLTAGE W/
PRIMARY = NEMA 5-15 (ENP5151) HAZARDOUS LOCATION
PLUG & SECONDARY = NEMA 5-20 (UGRP-20231F)
RECEPTACLES (QTY 4)



Key features



- Designed to meet NEC and OSHA Code Requirements for LV Lighting when used in Damp or Confined Space Applications
- Transformers, in corrosion resistant, impact resistant non metallic enclosures, convert 120vac to 12vac for areas where 12v is required
- Available in standard N5-15 receptacles or non-NEMA CF style for fixtures with dedicated 12vac lamps
- Portable transformers are available with 2 and 4 receptacles providing 12vac power - Each Receptacle is individually overload protected
- Portable Transformer is provided with standard N5-15, 120V Plug

Color	Gray
-------	------

UPC Code	782862900307
----------	--------------

Country of Origin	USA
-------------------	-----

Specifications

Category	Hazardous Location Grade
----------	--------------------------

Sub Category	Transformer - Low Voltage
--------------	---------------------------

Brand	Ericson
-------	---------

Technical Info

Bulb Type	LED 12V
Cable Length	6
Cable	14/3
Cable Type	SOW
Max Amps	15
Max Volts	12
Primary Cable End	NEMA 5-15 (ENP5151) Hazardous Location Plug
Secondary Cable End	NEMA 5-20R (UGRP-20231F) Receptacles (Qty 4)
NEMA Environment	Class I, Division 2 Groups B,C,D
Construction	Enclosed low voltage transformer in a fiberglass enclosure

Standards & Certifications

ETL	ETL Listed to UL 1012
cETL	cETL Listed to UL 1012

Shipping & Logistics Info

Pack/Unit Qty	1
HTS code	8504314035
ECCN	EAR99
Gross Weight (lbs)	25.00000
Length (in)	17
Warranty	1 Year

Accessories



PART#:
123100LEDXPI-5L



PART#:
123100LEDXPI-6L



Ericson Manufacturing Company
4323 Hamann Parkway
Willoughby, OH 44094, USA



1-800-374-2766
info@ericson.com

ericson.com