

1007-XP

EXPLOSION PROOF HIGH BAY LIGHT

STANDARD FEATURES:

- High efficacy: up to 140lm/W
- CRI>70
- Surface mounting and pendant installation
- Copper free aluminum
- High vibration resistance
- 5 year warranty
- Ambient temperature range: -40°C to 60°C

APPLICATIONS:


- Oil & gas industries
- Distilleries
- Paint manufacturing
- Pumping stations
- Mining
- Vessel lighting
- High humidity areas
- High temperature locations

RATINGS AND CERTIFICATIONS:


- NEMA 4X, IP66
- cETLus listed
- UL1598 / UL1598A / UL844
- CSA C22.2 No. 137/ No. 250.0
- Class I Division 1, Groups C, D
- Class I Division 2, Groups A, B, C, D
- Class II Division 1, Groups E, F, G
- Class II Division 2, Groups E, F, G
- Class III
- Wet locations
- T3 Temperature rating (150W)
- T4 Temperature rating (100W)



STRUCTURE DIAGRAM:



PHOTOMETRICS:



MODEL SELECTION GUIDE:

Product Number	Wattage	CCT	Voltage	Lumens	Working Hours	CRI
1007-XP-100	100	5000K	AC100-277V	14000	5 years	70
1007-XP-150	150	5000K	AC100-277V	21000	5 years	70