

Temporary Power Distribution Centers



e-Cart™ Jr.

- UL listed, QPS certified
- 480V or 600V, 3 phase or single phase 60Hz power input
- 15kVA epoxy encapsulated 3R transformer
- Output power options: 120Y/208V with 3-phase transformer or 120V/240V with single-phase transformer
- Combo load center with GFCI circuit breakers
- NEMA TYPE 3R main disconnect switch
- Twist lock closure
- Rain Guard flaps fold into cover
- Heavy-Duty cart with handle for easy maneuvering around job site
- 50A Receptacle
- Engineered solutions available, contact factory for more information

Exclusive NEMA type 3R Ericson engineered circuit breaker/receptacle “combo” enclosure panel.

- Combines circuit breaker panel with receptacle operation
- Heavy duty enclosure
- NEMA 3R rainproof “in use” flip top assembly

Selection Guide

Catalog Number	INPUT POWER				Secondary Info			OUTPUT CONNECTIONS			UL Listed
	Volts IN	Phase	Primary Connection	Transformer Size (kVA)	Secondary Voltage OUT	Secondary Panel MCB Installed	Panel and Connections Style	Receptacles Installed	Circuit & Personnel Protection		
EJR4115CL10600-UL	480	1	6 ft SOW Blunt	15	120/240	n/a	C	(6) 5-15/20 T Slot GFCI DPLX	(6) 20A STD BRKRS	YES	
EJR4115CM1061-UL	480	1	6 ft SOW Blunt	15	120/240	YES	C	(6) 5-15/20 T Slot GFCI DPLX & (1) CS6369 50A	50A ZP C.B. (6) 20A STD BRKRS	YES	
EJR4315CL30600-UL	480	3	6 ft SOW Blunt	15	120/208Y	n/a	C	(6) 5-15/20 T Slot GFCI DPLX	(6) 20A STD BRKRS	YES	
EJR4315CM30310-UL	480	3	6 ft SOW Blunt	15	120/208Y	YES	C	(3) 5-15/20 T Slot GFCI DPLX & (1) CS6369 50A	(3) 20A STD BRKRS & (1) 50A ZP C.B.	YES	
EJR4315CM3061-UL	480	3	6 ft SOW Blunt	15	120/208Y	YES	C	(6) 5-15/20 T Slot GFCI DPLX & (1) CS6369 50A	(6) 20A STD BRKRS & (1) 50A ZP C.B.	YES	
EJR4315CM31200-UL	480	3	6 ft SOW Blunt	15	120/208Y	YES	C	(12) 5-15/20 T Slot DPLX	(12) 20A GFCI C.B.	YES	



See the Video

