

# SERIES 422/452 ERSADUR DESOLDERING TIPS


■ DIGITAL 2000 A with CHIP TOOL  
■ MICRO-CON 60 iA with  
 SMD DESOLDERING PINCETTE 40

■ SMT UNIT 60 AC/A with CHIP TOOL/  
 SMD DESOLDERING PINCETTE 40

■ All i-CON stations with CHIP TOOL  
■ REWORK 80 / SMD 8000


## 0452FDLF040/SB

4 mm, for e.g. SO 8 GT/14 GT/16GT




## 0422ED/SB

6 mm, for e.g. SOIC 8




## 0452EDLF060/SB

6 mm, for e.g. SOIC 8




## 0452FDLF075/SB

7.5 mm, for e.g. SOIC 2/ SOT 23




## 0452FDLF100/SB

10 mm, for e.g. SOIC 16




## 0452FDLF125/SB

12.5 mm, for e.g. SOIC 20




## 0452FDLF150/SB

15 mm, for e.g. SOIC 24




## 0452FDLF200/SB

20 mm, for e.g. SOIC 32




## 0452FDLF250/SB

25 mm, for e.g. SOIC 40




## 0452QDLF100/SB

90° angle, length 10 mm, for e.g. PLCC 20




## 0452QDLF125/SB

90° angle, length 12.5 mm, for e.g. PLCC 28




## 0452QDLF150/SB

90° angle, length 15 mm, for e.g. QFP, TQFP and TTQFP 80T25




## 0452QDLF250/SB

90° angle, length 25 mm, for e.g. PLCC 68




## 0422MD/SB

ellipse, for MELF and MINI-MELF




## 0452MDLF020/SB

ellipse, for MELF and MINI-MELF



## 0422SD/SB

for MICRO-MELF



### \*Please note:

Tips 0422SD must be used in combination with the tip turn protection set to ensure good results.

Tip turn protection set for TC 40 desoldering tweezers and DESOLDERING PINCETTE 40 on request.