

SERIES 422/452 ERSADUR DESOLDERING TIPS


■ DIGITAL 2000 A with CHIP TOOL
■ MICRO-CON 60 iA with
SMD DESOLDERING PINCETTE 40

■ SMT UNIT 60 AC/A with CHIP TOOL/
SMD DESOLDERING PINCETTE 40

■ All i-CON stations with CHIP TOOL
■ REWORK 80 / SMD 8000


0452FDLF040/SB

4 mm, for e.g. SO 8 GT/14 GT/16GT




0422ED/SB

6 mm, for e.g. SOIC 8




0452EDLF060/SB

6 mm, for e.g. SOIC 8




0452FDLF075/SB

7.5 mm, for e.g. SOIC 2 / SOT 23




0452FDLF100/SB

10 mm, for e.g. SOIC 16




0452FDLF125/SB

12.5 mm, for e.g. SOIC 20




0452FDLF150/SB

15 mm, for e.g. SOIC 24




0452FDLF200/SB

20 mm, for e.g. SOIC 32




0452FDLF250/SB

25 mm, for e.g. SOIC 40




0452QDLF100/SB

90° angle, length 10 mm, for e.g. PLCC 20




0452QDLF125/SB

90° angle, length 12.5 mm, for e.g. PLCC 28




0452QDLF150/SB

90° angle, length 15 mm, for e.g. QFP, TQFP and TTQFP 80T25




0452QDLF250/SB

90° angle, length 25 mm, for e.g. PLCC 68




0422MD/SB

ellipse, for MELF and MINI-MELF




0452MDLF020/SB

ellipse, for MELF and MINI-MELF



0422SD/SB

for MICRO-MELF



*Please note:

Tips 0422SD must be used in combination with the tip turn protection set to ensure good results.

Tip turn protection set for TC 40 desoldering tweezers and DESOLDERING PINCETTE 40 on request.