

# ERSADUR long-life soldering tip series 612



- CPS 60.10
- DIGITAL 60 A
- DIGITAL 2000 A with TECH TOOL soldering iron
- MICRO-CON 60 iA with TECH TOOL soldering iron

<p><b>0612SDLF</b></p> <p>pencil point, 0.4 mm <math>\varnothing</math></p>	<p><b>0612UDLF</b></p> <p>pencil point, 0.8 mm <math>\varnothing</math></p>	<p><b>0612BDLF</b></p> <p>pencil point, 1.0 mm <math>\varnothing</math></p>	<p><b>0612CDLF</b></p> <p>chisel-shaped, 1.0 mm</p>
<p><b>0612ADLF</b></p> <p>chisel-shaped, 1.6 mm</p>	<p><b>0612KDLF</b></p> <p>chisel-shaped, 2.4 mm, bent</p>	<p><b>0612EDLF</b></p> <p>chisel-shaped, 3.2 mm <math>\varnothing</math></p>	<p><b>0612GDLF</b></p> <p>pencil point, 1.6 mm <math>\varnothing</math></p>
<p><b>0612JD</b></p> <p>chisel-shaped, 1.6 mm, bent 30°</p>	<p><b>0612ID</b></p> <p>pencil point, 0.4 mm <math>\varnothing</math>, bent 30°</p>	<p><b>0612MD</b></p> <p>PLCC blade, 1.5 mm</p>	<p><b>0612TW</b></p> <p>Ersa TechWell with concave portion, 3.0 mm</p>
<p><b>0612HD</b></p> <p>Ersa SolderWell with concave portion 2.5 mm, 30° bent</p>	<p><b>0612ZD</b></p> <p>WickTip, 10.5 x 3.6 mm</p>	<p><b>0612ND</b></p> <p>angled face, 3.0 mm, 45°</p>	<p><b>0612FDLF</b></p> <p>angled face, 2.0 mm, 45°</p>
<p><b>0612WDLF</b></p> <p>angled face, 4.0 mm, 45°</p>			

# Desoldering tip series 662

- ELS 8000/M/D
- ELS 8100
- MS 8100D



<p><b>0662AE</b></p> <p>ERSADUR, 1.2 mm <math>\varnothing</math> (for joints with medium heat requirements)</p>	<p><b>0662BE</b></p> <p>ERSADUR, 1.0 mm <math>\varnothing</math> (for joints with medium heat requirements)</p>	<p><b>0662CE</b></p> <p>ERSADUR, 0.8 mm <math>\varnothing</math> (for joints with medium heat requirements)</p>
---	---	---