

EVOKO MINTO

Glass Mounting Kit

Safety Instructions

Read all safety warnings and all instructions.

Failure to follow the warnings and instructions may result in serious injury.

Save all warnings and instructions for future reference.

A correct mounting is extremely important and this is not the responsibility of Evoko.

Faulty mounting may result in injury to persons or damage to equipment. Evoko will not be responsible in any way if the product has been mounted incorrectly.

IMPORTANT!

- For mounting on smooth glass surfaces only!
- Make sure the surfaces are clean, dry and above 59°F / 15°C before mounting!
- Avoid mounting in direct sun light!

Please see details on other side.

Mounting & general information

- Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improves bond strength.
- To obtain optimum adhesion, the bonding surfaces must be clean, dry and well unified. Some typical surface cleaning solvents are isopropyl alcohol or heptane.*
- Ideal tape application temperature range is 70°F to 100°F [21°C to 38°C]. Initial tape application to surfaces at temperatures below 59°F (15°C) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.
- Avoid mounting in direct sun light.
- Store in original cartons at 70°F [21°C] and 50% relative humidity.
- If stored under proper conditions, product retains its performance and properties for two years from date of manufacture.
- Illustration of mounting is available on product box.

*Note: Carefully read and follow the manufacturer's precautions and directions for use when working with solvents. These cleaning recommendations may not be in compliance with the rules of certain air quality management districts in California; consult applicable rules before use.

Liability text

All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M and Evoko believes are reliable. However, many factors beyond 3M's/Evoko's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. Neither 3M or Evoko MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M or Evoko product is fit for a particular purpose and suitable for user's application. If the 3M and/or Evoko product is defective within the warranty period, your exclusive remedy and 3M's and Evoko's sole obligation will be, at Evoko's option, to replace the product or refund the purchase price.

Except where prohibited by law, 3M and Evoko will not be liable for any loss or damage arising from the 3M or Evoko product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability