

Delo connection manager



Seamless  
meeting  
connectivity

evoko™

# Delo connection manager a new way to have meetings

Delo connection manager is an innovative screen sharing hub with integrated charging, cable management and control of the meeting room equipment. It will help to create a seamless meeting experience for all participants without the need for software installations, cable adapters or power supplies. Simply plug in the USB-C cable to your device and press a button to start sharing and take control of room equipment such as camera, speakers and microphones. Up to 4 people can connect and charge at the same time and it is easily installed in BYOD rooms as well as MTR/Zoom/Google rooms. Always a reliable connection, fully powered laptops and a clutter free table!



## Vivid and helpful colors

Bright and vivid colors guide you during the meeting. In combination with the touch controller it allows the connected participant to control and switch who is sharing their screen and has control of the connected In-room equipment such as cameras, microphones and speakers.



Idle



Charging




Sharing



HDMI Ingest

evoko™

# Key features



## **Reliable and fast connection**

Stable connection with smooth video stream.



## **Easily share your screen**

Share your screen with the press of a button.



## **Charge your devices**

Connected devices are charged with up to 100W.



## **Connect to the equipment**

Access in room meeting equipment such as cameras, microphones and speakers.



## **Clutter free table**

A clean table with the built in cable management.



## **Plug-and-play**

Smooth meetings without software installations.

# Platform of your choice

Delo connection manager gives you a smooth and seamless setup for full on-site meetings as well as hybrid meetings. No matter what video conferencing platform you choose the experience will be stress free, with the benefit of increased productivity.

You can connect to any of the common platforms such as Microsoft Teams, Zoom and Google Meet.

You can also connect a Barco ClickShare or other wireless screen sharing system for a hybrid setup.

# SPECIFICATIONS

## GENERAL

- **Model Name:** Delo connection manager
- **Warranty :** 2 years
- **Type :** Meeting connectivity

## CONNECTIONS

### Cables

- 4pcs USB 3.1 Gen 2 C to C
- Max 20V 5A 100W
  - Length 2m, 1m above table

### Power Supply

- **Input:** 85 - 264V AC, 2,4A max, 1 meter AC-cord included.
- **Output:** 20V DC, 10A, 4-Pin DIN with locking mechanism.
- **Power:** 180W Max (4x USB-A + 4x USB-C)

### Connectivity Hub

- **USB Devices:** 2x USB-A 3.0 sockets for connecting devices such as speakers and cameras.
- **HDMI :** HDMI 2.0 for connecting display or projector.
- **Wifi :** (Management only)
  - 2.4GHz, 802.11 n
- **Ethernet :** (Management only)
  - RJ45, 100Mbit/s, Full-duplex

## FUNCTIONALITY

**USB -C Video In:** Alt-Mode DisplayPort 1.1 to 1.4 2 or 4 lanes (configurable). Max bandwidth 32 Gbit/s Up to HDR3

**HDMI Video Out :** HDMI 2.0b. HDCP 1.4 and 2.3. Max 18 Gbit/s output.

- 2 DP Lane mode: DP1.2 = 4K30Hz, DP 1.4 = 4K60Hz.
- 4 DP Lane mode: DP 1.2 = 4K60Hz.

### USB Pass-through:

- 2 DP Lane mode: USB 2.0 LS/FS/HS & USB 3.1, SS/5 Gbit/s.
- 4 DP Lane mode: USB 2.0 LS/FS/HS

**Charging USB-C:** 5V/3A, 9V/3A, 12V/3A, 15V/3A, 19,5V/5A, 20V/5A

### I/O ports:

- 2 x USB-A 2.0 for controller & accessories.

## ARTICLE NUMBERS

### Evoko Delo (EU cable)

- ECM1001EU

### Evoko Delo (US cable)

- ECM1001US

### Evoko Delo (UK cable)

- ECM1001UK

## SOFTWARE

Delo management console (PC & Mac application)

- In room or pre-installation management of the Delo connection manager.
- Setup Ethernet or Wifi for OTA updates and online management.
- Choose between different setups such as BYOD, integrated MTR or PC-based MTR.

## IN THE BOX

- Touch controller with light guide
- Connectivity hub
- 4x USB-C to C cables
- Power supply
- 4x cable weights
- Cable bag
- Mounting brackets

## SIZE AND WEIGHT

### Retail Sales kit package

- 310 x 290 x 120 mm  
[12.2 x 11.4 x 4.7 in]
- 4 kg [8.82 lbs]



## DIMENSIONS

