

## TECHNICAL DATA SHEET


Part#: 554TXC-US

Pliers - Lock-in Lead Forming - 1st bend .060"

Form one lead in and one lead out at the same time on most radial type components

The 554TXC-US 5.5" shear cutting and forming plier will form one lead in and one lead out at the same time on most radial type components. The added shear cutter saves component prep time. It is recommended for .025" diameter or smaller leads. It features an ergonomically molded antimicrobial Anti-Static grip (10<sup>10</sup> ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10 <sup>10</sup> ohms/sq
• Shape	Straight
• Type of Cut	Shear
• Cutting Capacity	.025"
• Blade Angle	
• Blade Length	.900"
• Body Width	0.42" (10.5mm)
• Body Height	
• OAL	5.5" (137.5mm)
• Weight (OZ)	5
• UPC	662847007507
• Schedule B	8203.20.60.30
• ECCN	EAR99
• UNSPSC Code	
• Country of Origin	USA
• Group	Cutters/Stress Relief Formers



**EXCELTA**<sup>®</sup>  
CORPORATION

**554TXC-US**  
Component Forming  
"Stress Relief Bender  
and Cutter"