

TECHNICAL DATA SHEET

Part#: 7247E

Cutters - Medium Taper Relieved Head - Optimum Flush - Short Handle
 Designed for cutting .040" soft wire leaving a small 'pinch' on the wire

The 7247E Lazer Line® medium tapered/relieved optimum flush cutter has a cutting capacity of .005" - .040" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. The CNC machining allows the joint surfaces to be perfect to allow for long life. The dual leaf springs provide a smooth action. It features a ergonomically molded antimicrobial Anti-Static grip (10^{10} ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10^{10} ohms/sq
• Shape	Taper Relieved Head
• Type of Cut	Optimum Flush
• Cutting Capacity	.005" - .040"
• Blade Angle	14.25°
• Blade Length	.36" (9mm)
• Body Width	0.42" (10.5mm)
• Body Height	.25"
• OAL	4.75" (118.75mm)
• Weight (OZ)	3
• UPC	662847009563
• Schedule B	8203.20.60.60
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Medium Cutters - 7000 Series

