

TECHNICAL DATA SHEET

Part#: 7248E

Cutters - Medium Taper Relieved Head - Laser Flush - Short Handle
 Designed for cutting .036" soft wire leaving no 'pinch' on the wire

The 7248E Lazer Line® medium tapered/relieved laser flush cutter has a cutting capacity of .001" - .036" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. The CNC machining allows the joint surfaces to be perfect to allow for long life. The dual leaf springs provide a smooth action. It features a ergonomically molded antimicrobial Anti-Static grip (10¹⁰ ohms/sq surface resistivity) with dual leaf springs.

- Precision Level ★★★★★
- Material Carbon
- Surface Resistivity 10¹⁰ ohms/sq
- Shape Taper Relieved Head
- Type of Cut Lazer Flush
- Cutting Capacity .001 - .036"
- Blade Angle 14.25°
- Blade Length .36" (9mm)
- Body Width 0.42" (10.5mm)
- Body Height .25"
- OAL 4.75" (118.75mm)
- Weight (OZ) 3
- UPC 662847009587
- Schedule B 8203.20.60.60
- ECCN EAR99
- UNSPSC Code 27111511
- Country of Origin USA
- Group Medium Cutters - 7000 Series

