



600A AC/DC Clamp+MultiMeter

Autoranging pocket size clamp-on in rugged housing

Simultaneously displays Frequency with Current or Voltage

Features:

- Large 2400 count display (4999 counts for Hz)
- Clamp jaws open to 1.2" (30mm), 350MCM
- · Compact, rugged clamp-on with splash resistant front panel design
- Measure AC/DC Current and Voltage, Frequency and Resistance
- · Auto or manual ranging with Data Hold and Relative mode
- Continuity beeper and Diode test
- · Overload protection on all ranges
- Complete with test leads, two 1.5V AA batteries and carrying case





Specifications	Range	Max. Resolution	Basic Accuracy (%rdg+digits)
AC Current	600A	0.1A	$\pm (2\% + 5d)$
DC Current	600A	0.1A	$\pm (2\% + 8d)$
AC Voltage	600V	0.001V	$\pm (1.2\% + 5d)$
DC Voltage	600V	0.1mV	±(1% + 2d)
Resistance	$40 M\Omega$	0.1Ω	±(1% + 5d)
Frequency	100kHz	0.01Hz	$\pm (1\% + 5d)$
Continuity	<10 Ω , beeper will sound		
Diode test	yes		
Power	two 1.5V AA Batteries		
Dimensions	7.0 x 2.5 x 1.3" (178 x 64 x 33mm)		
Weight	8oz (230g)		

Ordering Information:

......600A AC/DC Clamp+MultiMeter 38394-NIST600A AC/DC Clamp+MultiMeter with Calibration Traceable to NIST 480172AC Line Separator

381277Temperature Adaptor, K probe





