

## EasyView™ Dual Input Thermometers

**Choice of Basic Type K or Datalogger model**  
*Datalogger model (EA15) compatible with 7 Types of Thermocouples*

### Features:

- Compact and rugged design features large backlit display
- Displays [T1 plus T2] or [T1-T2 plus T1] or [T1-T2 plus T2]
- Selectable units of °F, °C, K (Kelvin)
- Wide temperature range with 0.1°/1° resolution
- Timer function displays elapsed time plus the time when MIN and MAX readings are taken
- Data Hold function freezes reading on display
- Auto Power off to save battery life
- Low battery and overrange indication
- Records Max/Min readings for later recall
- Complete with built-in stand, protective holster, two Type K bead wire temperature probes (-22 to 572°F/-30 to 300°C), and 6 AAA batteries



EA10 Type K Dual Input Thermometer

EA15 Dual Input, 7 Thermocouple Type Thermometer Datalogger. Software included

### Model EA10

#### Features:

- Basic Type K Dual input
- OFFSET key used for zero function to make relative measurements

### Model EA15

#### Features:

- Dual input accepts Types J, K, E, T, R, S, and N thermocouples
- Built-in datalogger stores up to 8800 data sets
- RS-232 port to transfer data to PC for analysis
- Real Time Clock
- Includes Windows<sup>®</sup> 95/98/NT/2000/ME/XP/7 compatible software and cable

| Specifications    | EA10                             | EA15  |
|-------------------|----------------------------------|---|
| Thermocouple Type | EA10                             | EA15  |
| J                 | —                                | -200 to 1994°F (-150 to 1090°C)   |
| K                 | -200 to 1999°F (-200 to 1360°C)  | -200 to 1999.9°F (-150 to 1370°C)   |
| T                 | —                                | -200 to 752°F (-150 to 400°C)   |
| E                 | —                                | -200 to 1598°F (-150 to 870°C)  |
| R                 | —                                | 35 to 1999.9°F (2 to 1767°C)  |
| S                 | —                                | 35 to 1999.9°F (2 to 1767°C)  |
| N                 | —                                | -200 to 1999.9°F (-150 to 1300°C)   |
| Resolution        | 0.1°                             | 0.1°  |
| Basic Accuracy    | ±0.3% (+2°F/+1°C)                | ±0.05% rdg (+1.5°F/+0.75°C) Types J,K,E,T,N<br>±0.05% rdg (+4°F/+2°C) Types R,S |
| Dimensions        | 6 x 2.8 x 1.5" (152 x 72 x 37mm) | 6 x 2.8 x 1.5" (152 x 72 x 37mm)  |
| Weight            | 8.3oz (235g)                     | 8.3oz (235g)  |

### Ordering Information:

- EA10 .....EasyView<sup>®</sup> Dual K Thermometer  
 EA10-NIST .....EA10 with Certificate of Calibration Traceable to NIST  
 EA15 .....EasyView<sup>®</sup> Dual Input 7 Thermocouple Type Temperature Datalogger  
 EA15-NIST .....EA15 with Certificate of Calibration Traceable to NIST  
 409996 .....Soft Vinyl Pouch