

P/N: 1910586ACC

Copyright

© 2020, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: 1910586ACC

Commit: 60100

Language: en-US

Modified: 2019-10-03

Formatted: 2020-10-27

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
This cable is used, when a separate power supply is used (not the one supplied with the camera)	
Physical data	
Weight	75 g (2.6 oz.)
Cable length	2.0 m (6.6 ft.)
Connector	Pigtailed
Color	Black
Shipping information	
Packaging, type	Cardboard box
Packaging, weight	163 g (5.7 oz.)
Packaging, size	170 × 64 × 75 mm (6.69 × 2.52 × 2.95 in.)
EAN-13	7332558006375
UPC-12	845188006723
Country of origin	Taiwan

Compatible with the following products:

- 48201-1001; FLIR A300
- 42701-1001; FLIR A300 (9 Hz)
- 48201-1101; FLIR A310
- 42701-1101; FLIR A310 (9 Hz)
- 48001-1101; FLIR A315
- 48201-1201; FLIR A320 Tempscreen
- 42701-1201; FLIR A320 Tempscreen (9 Hz)
- 48001-1001; FLIR A325sc
- 61201-1003; FLIR A300f 25°
- 61201-1004; FLIR A300f 45°
- 61201-1102; FLIR A310f 15°
- 61201-1103; FLIR A310f 25°
- 61201-1104; FLIR A310f 45°
- 61201-1101; FLIR A310f 6°
- 61201-1105; FLIR A310f 90°
- 55001-0101; FLIR A615 15°
- 55001-0102; FLIR A615 25°
- 55001-0103; FLIR A615 45°
- 55001-0104; FLIR A615 7°
- 55001-0105; FLIR A615 80°
- 55001-0301; FLIR A655sc 15°
- 55001-0302; FLIR A655sc 25°



Power cable, pigtailed

P/N: 1910586ACC

© 2020, FLIR Systems, Inc.

#1910586ACC; r. 60100; en-US

- 55001-0303; FLIR A655sc 45°
- 55001-0304; FLIR A655sc 7°
- 55001-0305; FLIR A655sc 80°