

P/N: T198506

Copyright

© 2015, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T198506

Release:

Commit: 26732

Language: en-US

Modified: 2015-06-12

Formatted: 2015-11-03

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
High capacity battery for the IR camera.	
Power system	
Battery type	Rechargeable Li ion battery
Battery voltage	3.7 V
Battery capacity	7.8 Ah
Charging system	In camera (AC adapter or 12 V from a vehicle) or 2-bay charger
Charging time	2.5 h to 90% capacity, charging status indicated by LED's
Charging temperature	0°C to +45°C (+32°F to +113°F)
Environmental data	
Battery storage temperature range	-40°C to +70°C (-40°F to +158°F)
Physical data	
Battery weight	0.173 kg (0.38 lb.)
Size (L x W x H)	84 x 49 x 60 mm (3.3 x 1.9 x 2.4 in.)
Shipping information	
Packaging, type	Cardboard box
Packaging, weight	0.272 kg (0.6 lb.)
Packaging, size	183 x 136 x 63 mm (7.2 x 5.4 x 2.5 in.)
EAN-13	7332558004456
UPC-12	845188004453
Country of origin	Sweden

Compatible with the following products

- 72501-0101; FLIR T1020 12°
- 72501-0102; FLIR T1020 28°
- 72501-0103; FLIR T1020 45°
- 72501-0201; FLIR T1030sc 12°
- 72501-0202; FLIR T1030sc 28°

P/N: T198506

© 2015, FLIR Systems, Inc.

#T198506; r. /26732; en-US

- 72501-0203; FLIR T1030sc 45°
- 72501-0301; FLIR T1040 12°
- 72501-0302; FLIR T1040 28°
- 72501-0303; FLIR T1040 45°
- 72501-0401; FLIR T1050sc 12°
- 72501-0402; FLIR T1050sc 28°
- 72501-0403; FLIR T1050sc 45°
- 55903-0922; FLIR T600 15° (incl. Wi-Fi)
- 55903-1022; FLIR T600 25° (incl. Wi-Fi)
- 55903-1522; FLIR T600 45° (incl. Wi-Fi)
- 55903-2822; FLIR T600bx 25° (incl. Wi-Fi)
- 55903-2922; FLIR T600bx 45° (incl. Wi-Fi)
- 55903-8022; FLIR T610 15° (incl. Wi-Fi)
- 55903-3922; FLIR T610 25° (incl. Wi-Fi)
- 55903-4022; FLIR T610 45° (incl. Wi-Fi)
- 55903-5022; FLIR T620 15° (incl. Wi-Fi)
- 55903-5122; FLIR T620 25° (incl. Wi-Fi)
- 55903-5222; FLIR T620 45° (incl. Wi-Fi)
- 55903-5622; FLIR T620bx 15° (incl. Wi-Fi)
- 55903-5722; FLIR T620bx 25° (incl. Wi-Fi)
- 55903-5822; FLIR T620bx 45° (incl. Wi-Fi)
- 55904-6222; FLIR T630 15° (incl. Wi-Fi)
- 55904-6322; FLIR T630 25° (incl. Wi-Fi)
- 55904-6422; FLIR T630 45° (incl. Wi-Fi)
- 55904-8023; FLIR T630sc 15° (incl. Wi-Fi)
- 55904-8123; FLIR T630sc 25° (incl. Wi-Fi)
- 55904-8223; FLIR T630sc 45° (incl. Wi-Fi)
- 55904-6822; FLIR T640 15° (incl. Wi-Fi)
- 55904-6922; FLIR T640 25° (incl. Wi-Fi)
- 55904-7022; FLIR T640 45° (incl. Wi-Fi)
- 55904-7422; FLIR T640bx 15° (incl. Wi-Fi)
- 55904-7522; FLIR T640bx 25° (incl. Wi-Fi)
- 55904-7622; FLIR T640bx 45° (incl. Wi-Fi)
- 55904-7723; FLIR T650sc 15° (incl. Wi-Fi)
- 55904-7823; FLIR T650sc 25° (incl. Wi-Fi)
- 55904-7923; FLIR T650sc 45° (incl. Wi-Fi)
- 55904-8422; FLIR T660 15° (incl. Wi-Fi)
- 55904-8522; FLIR T660 25° (incl. Wi-Fi)
- 55904-8622; FLIR T660 45° (incl. Wi-Fi)

