

P/N: T199347ACC

Copyright

© 2021, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T199347ACC

Commit: 60015

Language:

Modified: 2019-10-02

Formatted: 2021-04-01

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
Rugged, watertight plastic shipping case for FLIR T5xx series, FLIR T8xx series, and FLIR GF7x series. Holds all items neatly and securely.	
Physical data	
Weight	2.5 kg (5.5 lb.)
Size (L x W x H)	484 x 345 x 178 mm (19.1 x 13.6 x 7.0 in.)
Material	PP with Rubber Blend (Polypropylene)
Color	Black
Shipping information	
Packaging, type	Cardboard box
List of contents	<ul style="list-style-type: none"> Hard transport case
Packaging, weight	2.9 kg (6.4 lb.)
Packaging, size	495 x 370 x 192 mm (19.5 x 14.6 x 7.6 in.)
EAN-13	4743254003392
UPC-12	845188014810
Country of origin	Italy

Compatible with the following products:

- 85201-0102; FLIR GF77 LR 25°
- 85202-0102; FLIR GF77 HR 25°
- 85203-0102; FLIR GF77 LR 25° + HR 25°
- 85204-0102; FLIR GF77 LR 25° + LR 6°
- 85205-0102; FLIR GF77 HR 25° + HR 6°
- 85206-0102; FLIR GF77 LR 25° + HR 25° + HR 6°
- 85207-0102; FLIR GF77 LR 25° + HR 25° + LR 6°
- 85208-0102; FLIR GF77 LR 25° + HR 25° + LR 6° + HR 6°
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°
- 79305-0201; FLIR T540 24° + 42°



Hard transport case

P/N: T199347ACC

© 2021, FLIR Systems, Inc.

#T199347ACC; r. 60015;

- 79303-0201; FLIR T540 42°
- 79307-0201; FLIR T540 42° + 14°
- 89001-0101; FLIR T560 14°
- 89002-0101; FLIR T560 24°
- 89004-0101; FLIR T560 24° + 14°
- 89006-0101; FLIR T560 24° + 14° & 42°
- 89005-0101; FLIR T560 24° + 42°
- 89003-0101; FLIR T560 42°
- 89007-0101; FLIR T560 42° + 14°
- 79302-0302; FLIR T540-EST 24°
- 79303-0302; FLIR T540-EST 42°
- 89002-0302; FLIR T560-EST 24°
- 89003-0302; FLIR T560-EST 42°
- 82501-0201; FLIR T840 14°
- 82502-0201; FLIR T840 24°
- 82504-0201; FLIR T840 24° + 14°
- 82506-0201; FLIR T840 24° + 14° & 42°
- 82505-0201; FLIR T840 24° + 42°
- 82503-0201; FLIR T840 42°
- 82507-0201; FLIR T840 42° + 14°
- 89201-0101; FLIR T860 14°
- 89202-0101; FLIR T860 24°
- 89204-0101; FLIR T860 24° + 14°
- 89206-0101; FLIR T860 24° + 14° & 42°
- 89205-0101; FLIR T860 24° + 42°
- 89203-0101; FLIR T860 42°
- 89207-0101; FLIR T860 42° + 14°
- 89201-0201; FLIR T865 14°
- 89202-0201; FLIR T865 24°
- 89204-0201; FLIR T865 24° + 14°
- 89206-0201; FLIR T865 24° + 14° & 42°
- 89205-0201; FLIR T865 24° + 42°
- 89203-0201; FLIR T865 42°
- 89207-0201; FLIR T865 42° + 14°