

P/N: T911855ACC

Copyright

© 2021, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T911855ACC

Commit: 64988

Language:

Modified: 2020-03-31

Formatted: 2021-07-06

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
Ethernet cable, M12 to RJ45, X-coded.	
Physical data	
Weight	0.489 kg (1.08 lb)
Cable length	10 m (32.8 ft)
Connector	M12 to RJ45
Color	Light grey
Shipping information	
Packaging, type	Cardboard box
Packaging, weight	0.649 kg (1.43 lb)
Packaging, size	220 × 160 × 75 mm (8.66 × 6.30 × 2.95 in)
EAN-13	7332558025901
UPC-12	845188021740

Compatible with the following products:

- 89995-0101; FLIR A70 Thermal Core 95°
- 89951-0101; FLIR A70 Thermal Core 51°
- 89929-0101; FLIR A70 Thermal Core 29°
- 89995-0201; FLIR A70 95° Research & Development Kit
- 89951-0201; FLIR A70 51° Research & Development Kit
- 89929-0201; FLIR A70 29° Research & Development Kit
- 89895-0101; FLIR A50 Thermal Core 95°
- 89851-0101; FLIR A50 Thermal Core 51°
- 89829-0101; FLIR A50 Thermal Core 29°
- 89895-0201; FLIR A50 95° Research & Development Kit
- 89851-0201; FLIR A50 51° Research & Development Kit
- 89829-0201; FLIR A50 29° Research & Development Kit
- 85900-0000; FLIR A700 Thermal Core
- 85901-0101; FLIR A700-EST 24°
- 85902-0101; FLIR A700-EST 42°
- 85902-0102; FLIR A700 24° Professional Science Kit
- 85902-0202; FLIR A700 24° Standard Science Kit
- 90600-0000; FLIR A500 Thermal Core
- 90601-0101; FLIR A500-EST 24°
- 90602-0101; FLIR A500-EST 42°
- 91900-0000; FLIR A400 Thermal Core
- 91902-0202; FLIR A400 24° Standard Science Kit
- 91903-0102; FLIR A400 24° Professional Science Kit
- 86401-0101; FLIR GF77a 25° LR
- 86403-0101; FLIR GF77a 6° LR