



\$FLIR

WE ARE HEAT-SEEKERS

Thermal energy is just a fancy way to say "heat." Thermal cameras detect heat, which means they don't need visible light to see. And nobody knows thermal imaging like we do. Militaries around the world have relied on our technology for years, and thermal cameras aren't strictly military hardware anymore.









FLIR [FLEER]

NOUN

- 1. The largest designer and producer of thermal imaging cameras, components and sensors globally.
- 2. The World's Sixth Sense


Over the past 40 years, FLIR has produced and delivered over 100,000 FLIR sensors, and thousands more radars and CBRNE sensors, for customers in more than 75 nations. This rich history of delivering the most technologically advanced solutions now also enables FLIR to provide quality products for professional and personal use.

\$FLIR

THERMAL 101

2015







LS-SERIES

The FLIR LS-X Series is a rugged combination of affordability, performance, and reliability that fits comfortably in the palm of your hand, whether you're on patrol or in pursuit. And now, the LS-XR features crisp 640 resolution and video out.





HS-SERIES

Featuring a 320×240 sensor, the HS-Series delivers enhanced imagery so law enforcement professionals can see even more of their surroundings. The HS-Series is available with a 19mm or 65 mm lens for greater range, and has optional on-board video / image recording (pro models only).



BHS-SERIES

Building on the power of the HS-Series, the BHS-Series is a bi-ocular that features swappable 35, 65, and 100 mm lenses and a choice of 320 or 640 sensors for maximum range performance, especially for surveillance and stealth operations.

FOR COMPLETE PRODUCT LINE AND SPECS SEE PAGES 12-15

\$FLIR

LAW ENFORCEMENT

2015







RECON M24

A basic, low-cost thermal pocket scope for tactical observation and general purpose night vision. Rugged and submersible, the Recon M24 provides a standard 320x240 image with optional 640x480 capability.



RECON M18

A full-featured, high performance pocket tactical scope with a standard 640x480 imager, remote video output and available laser pointer. Like the Recon M24, the Recon M18 is MIL-hardened and submersible, with low power consumption for long battery life.





THERMOSIGHT™ T70 AND T75

An uncooled weapon sight that doubles as a portable reconnaissance scope. Designed to interface with scopes such as the Trijicon ACOG for the M-4, M-16, and similar weapons.

FOR COMPLETE PRODUCT LINE AND SPECS SEE PAGES 12-15

\$FLIR

MILITARY

2015







SCOUT II

A compact, lightweight hand-held thermal camera, Scout II provides clear, crisp thermal imagery from dawn to dusk — and through the dead of night. And now, Scout II features a 640 resolution display and video out (320 model).





SCOUT TS

The TS-Series provides exceptional thermal performance and value. With resolutions of 240 or 320, the TS-Series is available with a 19 mm or 65 mm lens (TS32R only), and optional on-board video. It's the perfect tool for expedition leaders, wildlife management professionals, and ranchers to observe animals at night.



SCOUT BTS

The Scout BTS Bi-Ocular camera offers outdoor enthusiasts the ultimate in thermal imaging, using both eyes. Available with a 320 or 640 sensor, the BTS-Series features swappable 35, 65, and 100 mm lenses, a full-coverage eyepiece, and ergonomic comfort.

FOR COMPLETE PRODUCT LINE AND SPECS SEE PAGES 12-15

\$FLIR

VARMINT HUNTING

2015

GET 'EM WHILE THEY'RE HOT

Some beasts just don't belong around here. They're bad for the livestock, the scenery and the environment. And sometimes they need to receive that message in no uncertain terms. Thermal night vision rifle scopes help send it loud and clear.

Field Notes

Varmints can destroy or unbalance a healthy habitat. Predator animals can threaten single livestock or entire herds. But they can't hide from FLIR thermal scopes.







THERMOSIGHT™ R-SERIES

The world's most affordable line of commercial night vision rifle scopes for non-game hunting. Compact and easy to use, the R-Series delivers rock-solid thermal imaging to see predators and varmints in zero light.

FOR COMPLETE PRODUCT LINE AND SPECS SEE PAGES 12-15

\$FLIR

VARMINT HUNTING

2015

LAW ENFORCEMENT & TACTICAL

2015







SPECS	LS-X	LS-XR	HS-324	
DETECTOR	336 x 256	640 x 512	320 x 240	
LENS	19 mm	35 mm	19 mm / 2X Extender	
FIELD OF VISION	17° x 13°	18° x 14°	24° x 18°	
ZOOM	2x & 4x	2x, 4x, & 8x	2x	
DETECTION RANGE Man-Sized Target	625 yds. (570 m)	1250 yds. (1140 m)	480 yds. (440 m)	
VIDEO CAPABLE	NTSC Video Out (PAL with GUI)	NTSC Video Out (PAL with GUI)	NTSC or PAL Video Out	







SPECS	HS-307	BHS-X COMMAND	BHS-XR COMMAND
DETECTOR	320 x 240	320 x 240	640 x 480
LENS	65 mm	35 / 65 / 100 mm	35 / 65 / 100 mm
FIELD OF VISION	7° x 5°	13° x 10° / 7° x 5° / 5° x 3°	13° x 10° / 10° x 8° / 6° x 4°
DETECTION RANGE Man-Sized Target	1695 yds. (1550 m)	910 yds. / 1695 yds. / 2625 yds. (830 m / 1550 m / 2400 m)	1140 yds. / 2080 yds. / 3225 yds. (1040 / 1900 / 2950 m)
ZOOM	2x	2x	2X & 4x
VIDEO CAPABLE	NTSC or PAL Video Out	NTSC or PAL Video Out	NTSC or PAL Video Out













SPECS	MILSIGHT S135 (MUNS)	MILSIGHT T105 UNS	MILSIGHT T90 (TaNS)	
SENSOR	2	 ²	J ²	
FIELD OF VIEW	10°	13°	14h°	
WEIGHT	3.12 lbs. (1.45 kg)	2 lbs. (0.9 kg)	2 lbs. (0.9 kg)	
DIMENSIONS	8.7" long	7.29"	5.6"	
POWER	2 AA batteries / 8 hours	2 AA batteries	AA or CR123	











SPECS	RECON M18 (640)	RECON M18 (320)	RECON M24	Т70	T75
SENSOR	640 x 480	320 x 240	320 x 240, 640 x 480 (optional)	640 x 512	640 x 512
FIELD OF VIEW	18.7° x 14° (standard)	13.8° x 10° (optional)	24° x 18°	18.8° x 15° (1/2x) 9.4° x 7.5° (1x) 4.7° x 3.75° (2x)	9.4° x 7.5°
WEIGHT	1 lb. (~480 grams)	1 lb. (~480 grams)	.875 lbs. (.397 kg)	1.5 lbs. (.68 kg) with batteries / hardware	1.75 lbs. (0.79 kg) with batteries / hardware
DIMENSIONS	5" (L) x 3.25" (W) x 2.25" (H)	5" (L) x 3.25" (W) x 2.25" (H)	4.6" (L) x 3" (H) x 2.5" (W)	6.8" (L) X 3.4" (W) X 3.2° (H)	7.3" (L) X 2.8" (W) X 3.5" (H)
SHOCK MITIGATION SYSTEM	No	No	No	Yes	Yes
SHOCK AND VIBE	MIL-STD-810F, >3 meters	MIL-STD-810F, >3 meters	MIL-STD-810F, >3 meters	MIL-STD-810F, >3 meters	MIL-STD-810F, >3 meters
POWER	Two 3V CR123 batteries, >3 hours at room temp	Two 3V CR123 batteries, >3 hours at room temp	Two 3V CR123 batteries, <3 hours	1 or 2 CR123 batteries; 2 or 3 AA batteries / 6 hours	2 or 3AA (Lithium or alkaline); 1 or 2 CR123 batteries / 6 hours

OUTDOOR & HUNTING

2015









SPECS	SCOUT II 240	SCOUT II 320	SCOUT TS 24 / PRO	SCOUT TS 32 / PRO
DETECTOR	240 x 180	320 x 240	240 x 180	320 x 240
LENS	13 mm	19 mm	19 mm / with 2x Extender	19 mm / with 2x Extender
FIELD OF VISION	24° x 18°	17° x 13°	24° x 18° / 12° x 9°	24° x 18° / 12° x 9°
DETECTION RANGE Man-Sized Target	383 yds. (350 m)	600 yds. (550 m)	350 yds. / 600 yds. with Extender (320 m / 550 m)	480 yds. / 960 yds. with 2x Extender (440 m / 880 m)
ZOOM	No	2x	No / 2x (Pro)	2x
VIDEO CAPABLE	No	NTSC Video Out	NTSC or Pal Video out / SD card	NTSC or Pal Video out / SD card







SPECS	SCOUT TS 32R / PRO	SCOUT BTS-X PRO	SCOUT BTS-XR PRO
DETECTOR	320 x 240	320 x 240	640 x 480
LENS	65 mm	35 / 65 / 100 mm	35 / 65 / 100 mm
FIELD OF VISION	7° x 5°	13° x 10° / 7° x 5° / 5° x 3°	13° x 10° / 10° x 8° / 6° x 4°
DETECTION RANGE Man-Sized Target	1695 yds. (1550 m)	910 yds. / 1695 yds. / 2625 yds. (830 m / 1550 m / 2400 m)	1140 yds. / 2080 yds. / 3225 yds. (1040 m / 1900 m / 2950 m)
ZOOM	2x	2x	2x & 4x
VIDEO CAPABLE	NTSC or Pal Video out / SD card	NTSC or Pal Video out / SD card	NTSC or Pal Video out / SD card















SPECS	RS24 1X	RS32 1.25-5X	RS32 2.25-9X	RS32 4-16X	
DETECTOR	240 x 180	336 x 256	336 x 256	336 x 256	
LENS	13 mm	19 mm	35 mm	60 mm	
FIELD OF VISION	20°	16°	9°	5°	
ZOOM	No	Up to 4x	Up to 4x	Up to 4x	
VIDEO CAPABLE	No	NTSC Video Out	NTSC Video Out	NTSC Video Out	





SPECS	RS64 1.1-9X	RS64 2-16X
DETECTOR	640 x 512	640 x 512
LENS	35 mm	60 mm
FIELD OF VISION	18°	10°
ZOOM	2x, 4x, & 8x	2x, 4x, & 8x
VIDEO CAPABLE	NTSC Video Out	NTSC Video Out

NORTH AMERICA Oregon

27700 SW Parkway Ave. Wilsonville, OR 97070 USA 1-877-773-3547

Massachusetts

25 Esquire Road N. Billerica, MA 01862 USA 1-866-404-5627

EUROPE

The Netherlands

Charles Petitweg 214847 NW Teteringen Breda, The Netherlands +31 (0) 765 794 190

MIDDLE EAST/UAE

Dubai Airport Free Zone P.O. Box 54262 Office B-22 Street WB-21 Dubai United Arab Emirates +971 4 299 7218

SOUTH AMERICA Brazil

Av. Antonio Bardela 320 Sorocaba SP 18052-852 Brazil +55 (11) 3238 8070

ASIA/PACIFIC

China

K301-302, Building K, No 26 Lane 168 Daduhe Road Putuo District Shanghai 062 P.R. China +86-21-5469 7628

Australia

FLIR Systems Australia Pty Ltd Head Office10 Business Park Drive Notting Hill VIC 3168 Australia +61 3 9550 2800



1-877-596-6115 FLIR.COM sales@flir.com

