

Two-channel camera, 5.8 mm diameter with 1 m probe

P/N: VSC2-58-1FM

Copyright

© 2019, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: VSC2-58-1FM Commit: 55921 Language: en-US Modified: 2019-02-25 Formatted: 2019-07-31

Website

http://www.flir.com

Customer support

http://support.flir.com

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| Part No. General information | VSC2-58-1FM |
|--------------------------------------|--|
| General Information | |
| | |
| Short description | Two-channel camera, 5.8 mm diameter with 1 m probe |
| Compatible main unit | VS70 |
| Integrated handset | No |
| Wireless capabilities | N/A |
| Compatible wireless handset | With optional VST (cannot switch cameras with VST) |
| Compatible detachable cameras | N/A |
| Warranty | https://www.flir.com/testwarranty |
| Camera specifications | |
| Articulation | No |
| Diameter | 5.8 mm |
| Front camera focal length | 20–60 mm |
| Front camera field of view | 56° |
| Front camera resolution | QVGA (320×240) pixels |
| Side camera focal length | 20–60 mm |
| Side camera field of view | 56° |
| Side camera resolution | QVGA (320 \times 240) pixels |
| Probe length | 1 m |
| Video format | NTSC |
| Brightness control | Manual with variable options |
| Lamp type | LED |
| Power system | |
| Power requirements | N/A |
| Environmental data | |
| Operating temperature | -10 to 50°C (14-122°F) |
| Operating humidity | 80% maximum |
| Storage temperature | -40 to 80°C (-40 to 176°F) |
| Physical data | |
| Weight | See shipping information |
| Dimensions (H \times W \times L) | See shipping information |



Two-channel camera, 5.8 mm diameter with 1 m probe

P/N: VSC2-58-1FM

© 2019, FLIR Systems, Inc. #VSC2-58-1FM; r. 55921; en-US

| Physical data | |
|--|---|
| Material | PC-ABS, rubber hand grip, nylon strap |
| Color | Gray, black |
| Shipping information | |
| Packaging type | White box with FLIR accessory printing |
| Packaging contents | White box with FLIR accessory graphic, camera, camera attachment: anti-snag tip |
| Packaging weight | 0.35 kg |
| Packaging dimensions $(H \times W \times L)$ | 22 cm × 19 cm × 5 cm |
| Carton weight | 8.5 kg |
| Carton dimensions $(H \times W \times L)$ | 46 cm × 32 cm × 40 cm |
| Carton quantity | 24 |
| EAN-13 | 0793950400920 |
| UPC-12 | 793950400920 |
| Country of origin | TW |
| Tariff code | 9013909000 |
| Technical support | |
| Website | http://support.flir.com |