USB-EXT-1

1-Port USB 2.0 100m CAT 5e/6/7 Extender System with Flexible Power Set





DESCRIPTION

1-Port USB 2.0 100m CAT 5e/6/7 Extender System with Flexible Power

The USB-EXT-1 extends high-speed USB 2.0 connections up to 100m using CAT 5e/6/7 with the option to power either the Local Extender or Remote Extender.


The USB-EXT-1 is ideal for extending USB peripherals including: keyboards, mice, interactive whiteboards, flash drives, hard drives, audio devices, web cameras and any other USB device.

FEATURES

- Flexible power connect the power adapter to either the Local or Remote Extender
- Supplies up to 1 Amp to USB port
- Mass Storage Acceleration for USB 2.0 device bulk transfers
- Supports throughputs of up to 480 Mbps
- Transparent USB extension
- Plug and play; no software drivers required
- Works with all major operating systems: Windows®, macOS™ and Linux®

APPLICATIONS

- Interactive white board
- Sensor/data acquisition
- Keyboard and mouse extension
- Industrial control



FSR Inc.

244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207

Order Desk: 1-800-332-FSR1

Web: www.fsrinc.com · E-mail: sales@fsrinc.com











RANGE	Direct Connect:	Connect: Up to 100m (330 ft) over CAT 5e/6/7	
SPEEDS	USB 2.0:	Up to 480 Mbps	
	USB 1.1:	Up to 12 Mbps	
POWER	Power Supply: 00-240V AC Input, 24V 1A DC Output includ		
LOCAL EXTENDER	USB Connector:	1 x USB Type B Receptacle	
	Link Connector:	1 x RJ45	
	Dimensions:	65.0mm x 87.5mm x 30.0mm (2.6" x 3.4" x 1.2")	
	Mounting:	Slots for Cable Ties	
	Enclosure Material:	Black ABS with Rubberized Coating	
REMOTE EXTENDER	USB Connector:	1 x USB Type A Receptacle	
	Link Connector:	1 x RJ45	
	Available Current:	Up to 1 Amp to USB port	
	Dimensions:	65.0mm x 87.5mm x 30.0mm (2.6" x 3.4" x 1.2")	
	Mounting:	Slots for Cable Ties	
	Enclosure Material:	Black ABS with Rubberized Coating	
ENVIRONMENTAL	Operating Temperature:	0°C to 50°C (32°F to 122°F)	
	Storage Temperature:	-20°C to 70°C (-4°F to 158°F)	
	Operating Humidity:	20% to 80% relative humidity, non-condensing	
	Storage Humidity:	10% to 90% relative humidity, non-condensing	
COMPLIANCE	EMC:	FCC (Class A), CE (Class A)	
	Environmental:	RoHS2 (CE)	
	Safety:	Flammability V-0	
SUPPORT Warranty:		2-year	

ORDERING INFORMATION

Part #	Name	Description
18091	USB-EXT-1	1-Port USB 2.0 100m CAT 5e/6/7 Extender Set

FSR Inc.

244 Bergen Boulevard Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207

Order Desk: 1-800-332-FSR1 Web: www.fsrinc.com E-mail: sales@fsrinc.com