T6 FLEX

Touchboards 205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards

Room Control at your fingertips





DESCRIPTION

Encased in one of our elegant T6 table boxes the T6 Flex control system is a small, powerful and affordable solution perfect for nearly any installation. It features a 3.5" color LCD touchscreen and all of the connectivity needed to control the lighting, shades and every piece of AV equipment installed all from one central location.

It features the full complement of serial, IR, GPIO and Ethernet ports and is the right choice for larger installations or where network connectivity is required. The interior compartment can be populated with a variety of AC and AV connector plates available from FSR.

A Flex can also be remotely controlled using the Flex Remote Control software. The software connects to the Flex installed in the room and replicates the screen on the desktop and is available for: Windows 8®; Windows RT®; Windows Phone®; Android®; iPad® and iPhone®.


TARGET MARKETS


- K-12 Classrooms
- University Lecture Halls
- Boardrooms
- Meeting Rooms
- Conference Rooms

FEATURES

- 3.5" Diagonal Color LCD Touch Screen
- 4 Serial Ports
- 4 IR Ports (Each Can Control up to 4 Devices)
- 4 GPIO Ports
- IP Port
- Built In Clock / Calendar with Scheduler
- · Multi Command Scripting Conditionality
- "Power over Ethernet capability"

DIMENSIONS





244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207 Web: www.fsrinc.com · E-mail: sales@fsrinc.com

SPECIFICATIONS

Serial Ports (RS-232)

Speed: 2400-115,200 bps (Ports 1,2,3)

2400-57,600 bps (Port 4)

Pins: TX, RX and GND Connector type: Screw terminal

IR Ports

Connector type: Screw terminal

I/O Ports

Output: open collector, current limited to 100mA,

(24VDC max)

Input: $VIH_MIN = 5VDC$, $VIH_MAX = 24VDC$,

 $VIL_MAX = 0.4VDC$

Connector type: Screw terminal

Ethernet Port

Type: 10/100BASE T/X

Compliance and supported features:

Compliant with IEEE 802.3/802.3u (100BASE-TX) Compliant with ISO 802-3 / IEEE 802.3 (10BASE-T)

Supports Auto-negotiation

Supports Automatic polarity detection and correction

Supports HP Auto MDI/MDI-X (no crossover cables required)

Protocols TCP/IP, UDP

Connector type: RJ-45

Power

Local adapter
Voltage: 12VDC
Current: 500mA
Power supply included

Connector type: Screw terminal **Power over Ethernet (PoE)**

Compliant with IEEE 802.3af (Class I device)

Support local power adapter OR-ing for redundancy

(local adapter preference)

Unit can be powered from an 802.3af compliant PoE

switch (not provided)

Unit can be powered from an 802.3af compliant PoE PSE

adapter (i.e. midspan injector. Not included

(optional accessory)

See LIT1359 FLEX Brochure for additional application information.



T6 FLEX ORDERING INFORMATION

T6-FLEX Requires 2 Large and 1 Half Small Bracket – Select Large & Half Small Brackets Below			
Item #	Part #	Description	
17737	T6-FLEX-BLK	6" Table Box with Flex Control Unit- Round – Black (Chassis Only)	
17738	T6-FLEX-SQBLK	6" Table Box with Flex Control Unit- Square - Black (Chassis Only)	
17739	T6-FLEX-ALM	6" Table Box with Flex Control Unit- Round – Aluminum (Chassis Only)	
17740	T6-FLEX-SQALM	6" Table Box with Flex Control Unit- Square – Aluminum (Chassis Only)	
17741	T6-FLEX-BRS	6" Table Box with Flex Control Unit- Round – Brass (Chassis Only)	
17742	T6-FLEX-SQBRS	6" Table Box with Flex Control Unit- Square – Brass (Chassis Only)	
	ge Section Bracke Standard 3 Prong E	ts - Choose TWO dison Plug Mains = Hard Wired Electric Feed	HALF HEIGHT LARGE SECTION BRACKETS
17067	T6-LB-AC3	T6 Large Section Bracket w/ 3 AC Outlets - Edison	
17068	T6-LB-AC3HW	T6 Large Section Bracket w/ 3 AC Outlets - Mains	T6-LB-CP T6-LB-AC3 T6-LB-AC3HW
17069	T6-LB-4IPS	T6 Large Section Bracket w/ 2 x 2 Space IPS Openings	10-LB-CP 10-LB-AC3 10-LB-AC3HW
17070	T6-LB-5SS	T6 Large Section Bracket for 5 Snap In Connectors	
17071	T6-LB-CP	T6 Large Section Bracket for Cable Pull	
17639	T6-LB-RTMKT	T6 Large Section Bracket Mounting Kit (up to 4 Retractors)	T6-LB-4IPS T6-LB-5SS T6-LB-RTMKT
T6 Half Small Brackets - Choose ONE		SMALL SECTION BRACKETS	
17710	T6-HSB-2SS	T6-Flex, EURO Half Small – Bracket for 2 Snap-In Jacks	
17727	T6-HSB-1IPS	T6-Flex Half Small Bracket – Holds 1 IPS Insert	
17728	T6-HSB-CP	T6-Flex Half Small Bracket – Cable Pull Bracket	T6-HSB-1IPS T6-HSB-2SS T6-HSB-CP
Flex Accessories			
17093	FLEX-BATT	Battery Backup Kit	
17095	FLEX-PRGM	Programming Kit for FLEX w/ IR Learner	
17019	IR-EC1-6	Single IR Emitter w/ 6' Cable	
17295	FLEX-MGR	Flex Management Software Suite	



244 Bergen Boulevard, Woodland Park, NJ 07424 Phone: 973.785.4347 · Fax: 973.785.4207 Web: www.fsrinc.com · E-mail: sales@fsrinc.com



