

The G-34 moisture tester lets you easily check moisture levels in baled hops to assure highquality harvest and safe storage. The large analog display and built-in battery check make this a favorite among hop growers worldwide.



Your Benefits:

- Easy-to-read analog display
- Moisture Range: 7%-14% on hops
- Built-in battery and calibration check
- Auto-shutoff timer saves battery life
- Size: 19x10x7cm (7 3/8x3 7/8x2 3/4") •
- Weight: 450gr. (1 lb)
- Rugged construction ensures years of reliable use
- sturdy plastic carrying case
- 9V battery
- 1-year warranty

Available electrodes:





830-5

30-E/C

(9 1/2").

moisture.

Pen electrode specially for hops.

For testing standard and high density hop bales. (Requires H-4 Handle)

Electrode with 2 long

insulated pins of 24cm

ideal for measuring the

Thanks to the insulated

measuring the surface

the bale instead of

pins, you measure inside

The long insulated pins are

moisture content in bales.



H-4 Handle for electrode 830-5.

Recommended Accessory:



MCS-44 -

This moisture content standard is great for verifying that your G-34 hops moisture meter is in calibration. With two electrical resistance values (8% and 10%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy. The MCS-44 is also available with a letter of certification traceable to NIST.

ArtTest B.V. Tradename Delmhorst Europe www.MoistureMetersDelmhorst.com

Titaniumlaan 100 NL-5221 CK 's-Hertogenbosch The Netherlands

E. info@Delmhorst.eu T. 0031 73 639 5080 F. 0031 73 631 4625

VAT NL851405848B01 EORI no. NL851405848 Cham Comm. 54695910