

Series M Mechanical Tilt Float Level Switch




- ▶ Non-Mercury Switch
- ▶ Sealed Cable
- ▶ Impact & Corrosion Resistant ABS Shell
- ▶ N.O., N.C., SPDT Contacts
- ▶ Various Cable Lengths
- ▶ Color Coded Body

Designed for level control and alarm applications in difficult liquids such as sewage and waste water. Series M mechanical tilt floats are ideal for applications where the presence of mercury is a concern. Series M Switches have impact resistant ABS shell and neoprene jacketed cable.

Specifications

Cord	2 or 3 conductor 16 AWG wire SJOW Oil Resistant CPE
Contact Rating	13 amp @ 120/240 VAC 1/2 hp
Contact Design	SPST, Normally Open or Normally Closed Common with N.O. & N.C. (form C)
Temperature Rating	
Dry	32°F to 194°F (0°C to 90°C)
Water Resistant	32°F to 140°F (0°C to 60°C)
Overall Weight	1.0 lbs. (not including weight)
Tether Method	Tie-wrap nylon, weight: 2.5 lbs.
Approvals	U.L. Recognized, CSA Cert.

Dimensions




Applications

- Level Control
- Alarms
- Sewage Lift Systems
- Slurries
- Drainage Sumps
- Wastewater Treatment
- Holding Tanks

How to Order

Use the **Bold** characters from the chart below to construct a product code.



Tether Method	Part Number
Tie Wrap	7762360
Weight	7762381

Notes:

1. Narrow angle pumping range approximately 2 in. to 8 in.
2. Wide angle pumping range approximately 5 in. to 18 in.