

**GENERAL®**

# Pinless LCD Moisture Meter

**Ideal for measuring moisture content of wood and other construction materials**

**Features:**

- Non-invasive measurement technology
- Jumbo display
- Wide measurement range
- Intuitive on-screen icons: Low/Medium/High moisture content; wood/concrete mode
- Hold function
- Audible peak reading alert
- Auto-calibrating
- Auto power Off

**Specifications:****Ranges:**

0 to 99.9% WME (Wood Moisture Equivalent) for wood; 0 to 56.5% for building materials

**Accuracy/Resolution:** ±3%/0.1%

**Measuring Depth:** 3/4 in. (20mm)

**Auto Power Off Trigger:**

3 to 4 minutes with 0% reading

**Low/Very Low Battery Warning Triggers:**

<7.5V/<6.5V

**Operating Temperature:**

32° to 122°F (0° to 50°C)

**Operating Relative Humidity:** <80%

**Dimensions:**

6.6 x 3.0 x 2.7 in.  
(170 x 77 x 40mm)

**Weight:** 10.4 oz. (255g)

**Power Source:** 1 "9V" battery (included)



**Prevent Mold!**



**Teak planks become bendable and stable with 15% moisture**



**Locate moisture/water damage**

**No. MMD5NP**

**GENERAL®****General Tools & Instruments**

80 White Street, New York, NY 10013-3567

TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665

sales@generaltools.com www.generaltools.com

MMD5NPSS Printed in USA 05/13