

ACSR AND GUY WIRE CUTTERS

ESG55LX, ESG45LX

- Designed to cut the largest ACSR, ground rods, and guy strands
- Guillotine style head
- Equipped with retraction stop to aid in time and battery savings
- Hardened blades for increased longevity



ESG55LX

ESG55LX

CAT. NO.	UPC NO.	DESCRIPTION
ESG55LX11	61299	Wire Cutter, Li-ion, 55mm STD, 120V
ESG55LX12	61300	Wire Cutter, Li-ion, 55mm STD, 12V
ESG55LX22	61301	Wire Cutter, Li-ion, 55mm STD, 230V
ESG55LX120	61302	Wire Cutter, Li-ion, 55mm STD, 120V AC
ESG55LX230	61303	Wire Cutter, Li-ion, 55mm STD, 230V AC
ESG55LXB	61304	Wire Cutter, Li-ion, 55mm STD, Bare



SPECIFICATIONS

- Length: 18-1/8" (460mm)
- Width: 3-1/8" (80mm)
- Height: 13-1/4" (337mm)
- Weight: 17.5 lb. (8kg)

CAPACITY

- Max Diameter: 2-1/8" diameter
- ACSR: Joree 76/19 AWG Std
- Guy Strand: 5/8" diameter
- EHS Guy Strand: 9/16" diameter
- Ground Rod: 3/4" diameter
- Rebar (SCH 60): 5/8" diameter
- Soft Steel Bolts: 3/4" diameter

ERGONOMICS

- Handle angle supports decreased wrist deviation and increased grip strength
- Second handle allows for optimal weight distribution



ESG45LX

- Single trigger activation reduces repetitive motion injuries
- 350° head rotation enhances adjustability and reduces user effort

ESG45LX

CAT. NO.	UPC NO.	DESCRIPTION
ESG45LX11	61287	Wire Cutter, Li-ion, 45mm STD, 120V
ESG45LX12	61288	Wire Cutter, Li-ion, 45mm STD, 12V
ESG45LX22	61289	Wire Cutter, Li-ion, 45mm STD, 230V
ESG45LX120	61290	Wire Cutter, Li-ion, 45mm STD, 120V AC
ESG45LX230	61291	Wire Cutter, Li-ion, 45mm STD, 230V AC
ESG45LXB	61292	Wire Cutter, Li-ion, 45mm STD, Bare

ACCESSORIES

CAT. NO.	UPC NO.	DESCRIPTION
05167	05167	18V 4.0Ah Li-ion Battery
52178	52178	120V Li-ion Battery Charger
52179	52179	230V Li-ion Battery Charger
52180	52180	12V Li-ion Battery Charger
10118	10118	Carrying Case
12274	12274	Carrying Strap

SPECIFICATIONS

- Length: 16-5/8" (423mm)
- Width: 3-1/8" (80mm)
- Height: 13" (330mm)
- Weight: 13 lbs (5.9kg)

CAPACITY

- ACSR: 1590 kcmil (MCM), (Falcon 54/19)
- Standard Guy Strand: 5/8" diameter (16mm)
- EHS Guy Strand: 1/2" diameter (13mm)
- Ground Rod: 5/8" diameter (16mm)
- Rebar (schedule 60): 1/2" diameter (13mm)
- Wire Rope: 5/8" diameter (16mm)
- Copper and Aluminum