IN-LINE BOLT CUTTERS ETS12LX





- · In-line tool style is light weight and very easy to control
- · One trigger controls all tool functions
- Tools automatically retract when the cutting cycle is complete

SPECIFICATIONS

Height	13-5/8" (365 mm)
Width	2-7/8" (73 mm)
Weight	4.4 lb (2.0 kg)

CUTTING CAPACITY

Common Bolt	1/2" diameter
Grade 5 Bolt	7/16" diameter
Grade 8 Bolt	5/16" diameter
Threaded Rod	1/2" diameter
One-Time Disposable Lock	4 AWG Alumoweld
Boa Lock	BL-9
Grade 40 Rebar	3/8" diameter
Steel Rod	3/8" diameter (1/2" diameter using two cycles)
Ground Rod	3/8" diameter (1/2" diameter using two cycles)
Copper and Aluminum Cable	2/0 AWG
ACSR	3/0 AWG Pigeon (4/0 AWG Pigeon using two cycles)
Guy Strand	5/16" diameter (3/8" diameter using two cycles)
EHS Guy Strand	5/16" diameter
Aircraft Cable	1/4" diameter

ETS12LX

CAT NO.	UPC NO.	DESCRIPTION
ETS12LX11	783310611820	Cutter, 120V Charger, Two 2.0 Ah Batteries
ETS12LX12	783310611837	Cutter, 12V Charger, Two 2.0 Ah Batteries
ETS12LX22	783310611844	Cutter, 230V Charger, Two 2.0 Ah Batteries
ETS12LXB	783310611875	Cutter, Bare Tool Only
HB.9864	783310562887	Blade Set (ETS12LX)