

12-Ton Manual Hydraulic Crimping Tools



HK1230



- Both heads accept Greenlee KC12, KA12 and KD12 crimping dies as well as industry "U" style dies
- New head designs result in lower weight and improved durability – tested to 50,000 crimp cycles
- Two-speed pump to reduce cycle time
- Ram automatically retracts when crimp cycle is complete
- Crimping heads rotate 350°
- Smaller and lighter than competitive tools
- Covered head models have two layers of PVC that total approximately 3/16" (4.8 mm) thick
- Includes carrying case



HK1240



SPECIFICATIONS

Capacity*	HK1230 & HK1240 – 8 AWG to 750 kcmil copper color-coded lugs and splices. See Crimping Tool Capacities, page 313.
Crimping Force	24,000 lb (106 kN)
Length	HK1230 – 20-3/8" (518 mm) HK1240 – 21-1/2" (546 mm)
Weight	HK1230 – 12.2 lb (5.5 kg) HK1240 – 13.2 lb (6.0 kg)

*HK1230 and HK1240 are UL and cUL classified with Anderson, Blackburn, FCI Burndy, ILSCO, Panduit, Penn-Union and Thomas & Betts copper and aluminum color-coded lugs and splices when used with Greenlee KC12 and KA12 crimping dies.



HK1240C



CAT. NO.	UPC NO.	DESCRIPTION
HK1230	783310064268	12-Ton Hydraulic Crimping Tool, 1.2" (30 mm) opening
HK1230C	783310071990	12-Ton Hydraulic Crimping Tool, 1.2" (30 mm) opening, PVC covered
HK1240	783310064275	12-Ton Hydraulic Crimping Tool, 1.65" (42 mm) opening
HK1240C	783310072027	12-Ton Hydraulic Crimping Tool, 1.65" (42 mm) opening, PVC covered



Crimping Dies for 12-Ton Tools