

Specification Sheet

Part Number: 133-04044



Secures two routings together while keeping them separated, to prevent chafing or heat transfer
Inverted retaining legs and narrow opening prevent inadvertent disengagement
Controlled flex and angled entry promote easy installation
Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole
For use with routings of the following size: 2x 47-51mm

Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Article Number	133-04044
Type	PC5X2SO
Color	Black (BK)
Quantity Per	carton
Product Description	This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.
Short Description	Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Global Part Name	PC5X2SO-PA66HIRHS-BK
------------------	----------------------

Length L (Imperial)	0.97
---------------------	------

Length L (Metric)	23.74
-------------------	-------

Fixation Method	Arrowhead
-----------------	-----------

Width W (Imperial)	0.88
--------------------	------

Width W (Metric)	22.35
------------------	-------

Height H (Imperial)	1.14
---------------------	------

Height H (Metric)	28.9
-------------------	------

Panel Thickness Min (Imperial)	0.02
--------------------------------	------

Panel Thickness Max (Imperial)	0.04
--------------------------------	------

Panel Thickness Min (Metric)	0.6
------------------------------	-----

Panel Thickness Max (Metric)	1.0
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.24" x 0.27
-------------------------------------	--------------

Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
-----------------------------------	--------------

Mounting Hole Diameter D Min (Imperial)	0.24
---	------

Mounting Hole Diameter D Max (Imperial)	0.27
---	------

Mounting Hole Diameter D Max (Metric)	6.9
---------------------------------------	-----

Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
----------	--

Material Shortcut	PA66HIRHS
-------------------	-----------

UV Resistant (Yes/No)	No
-----------------------	----

Operating Temperature	-40°F to +230°F (-40°C to +110°C)
-----------------------	-----------------------------------

Reach Compliant (Article 33)	No
------------------------------	----

ROHS Compliant	Yes
----------------	-----

Package Quantity (Imperial)	5008
-----------------------------	------

Package Quantity (Metric)	5000
---------------------------	------

Customs Number	3926909988
----------------	------------

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

