




SW2015



Revision level			Revision Record	Changed	Date	Approved	Date
Drawing	State	Part					
00.1	Design Release	-	SEE ECN# 013916	CAS	6/15/2017	KAC	6/15/2017





STRIPPING LENGTH:
11MM(.45 IN)


WIRE RANGE:
22-12 AWG SOLID CU / 22 - 14 AWG STRANDED
0.5 TO 2.5MM² SOLID CU / 1.0 TO 2.5MM² STRANDED


FLAMMABILITY:
UL94 V0

WORKING TEMP:
-30°C (-22°F) TO 85°C (185°F)

VOLTAGE:
450V (VDE) 85°C
600V (CULUS) 105°C

CERTIFICATIONS:
UL E316080
KEMA-KEUR, VDE, FIMKO,
ENEC, CEBEC, NEMKO, DEMKO





Notes	Material POLYCARBONATE COLOR:BLUE	Units: millimeters Dimension without tolerances details to: .xxx = ±.013 .xx = ±.13 .x = ±.3 None = ±.8 ∠ = ±0.5° Dimension Formatted mm/[in]	The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.	Drawn	CAS	6/15/2017	Article/Type-No HCPM-5	Scale	1:1	
				Approved	KAC	6/15/2017		Title HELACON PLUS MINI PUSH-IN STYLE WIRE CONNECTOR, 5-PORT, BLUE	Project Number	PRP17-1032
				HellermannTyton North America Email: corp@htamericas.com Web: www.hellermann.tyton.com			Drawing-No		PRODUCTION : Phase	Format
							17-1032-001-CSU		Sheet	1/1