

Specification Sheet

Part Number: 151-10920



2- or 4-way entry options for the Q-Tie, offering flexibility and stability
Designed for use with 18- through 120-pound cable ties to provide stability when securing bundles.
Secures with a single screw, providing quick installation.

Article Number	151-10920
Type	CTQM5
Color	Natural (NA)
Quantity Per	bag
Product Description	Q-Series mounting bases are designed to work exclusively with the Q-Tie® cable tie series. This mounting component can be secured with screws. The Q-Mount allows either a two- or four-way entry for the Q-Tie, providing a quick and simple insertion into the mount. Once in place, the Q-Tie will not slip out, even in vertical mounting applications.
Short Description	Q Tie Mount, M4 Screw, 0.83" x 0.38" x 0.26", For Q18–Q50 ties, PA66, Natural, 100/bg
Global Part Name	CTQM5-PA66-NA

Length L (Imperial)	0.83
Length L (Metric)	21.0
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.38
Width W (Metric)	9.5
Cable Ties	Q-Ties
Height H (Imperial)	0.26
Height H (Metric)	6.7
Cable Tie Width Max (Imperial)	0.2
Cable Tie Width Max (Metric)	5.0
Mounting Hole Diameter D (Imperial)	0.175
Mounting Hole Diameter D (Metric)	4.5 mm
Mounting Hole Diameter D Min (Imperial)	0.18
Mounting Hole Diameter D Max (Metric)	4.5
Material	Polyamide 6.6 (PA66)

Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 746B UL ANSI/UL 1565 UL ANSI/UL 62275
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global

customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin.
(www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)