

## Specification Sheet

Part Number: 156-01295



Head allows for a 0.2" lateral adjustment on stud during installation.  
Quick and easy installation ideal for manufacturing environment.

|                     |                                                                                                                                                                                                                                                                                |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 156-01295                                                                                                                                                                                                                                                                      |
| Type                | T50R0SBS6USET                                                                                                                                                                                                                                                                  |
| Color               | Black (BK)                                                                                                                                                                                                                                                                     |
| Quantity Per        | carton                                                                                                                                                                                                                                                                         |
| Product Description | Oval Shaped Stud Mount's special design allows for a 0.2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools. |
| Short Description   | 2-Piece Cable Tie/Oval Stud Mount, 8.0" Long, 50lb Tensile, With Thumb Bar, PA66HIRHS, Black, 2000/box                                                                                                                                                                         |
| Global Part Name    | T50R0SBS6USET-PA66/PA66HIRHS-BK                                                                                                                                                                                                                                                |

|                                     |                  |
|-------------------------------------|------------------|
| Minimum Tensile Strength (Imperial) | 25.0             |
| Minimum Tensile Strength (Metric)   | 110              |
| Length L (Imperial)                 | 8.0              |
| Length L (Metric)                   | 203.2            |
| Fixation Method                     | Weld Stud Fixing |
| Identification Plate Position       | none             |
| Releasable Closure                  | No               |
| Tie Closure                         | plastic pawl     |
| Width W (Imperial)                  | 0.55             |
| Bundle Diameter Min (Imperial)      | 0.16             |
| Bundle Diameter Min (Metric)        | 4.0              |
| Bundle Diameter Max (Imperial)      | 1.97             |
| Bundle Diameter Max (Metric)        | 50.0             |
| Height H (Imperial)                 | 0.87             |
| Height H (Metric)                   | 21.5             |
| Mounting Hole Diameter D (Metric)   | M6 x 1           |

|                              |                                                                                          |
|------------------------------|------------------------------------------------------------------------------------------|
| Stud Diameter (Metric)       | M6                                                                                       |
| Material                     | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)<br>Polyamide 6.6 (PA66) |
| Material Shortcut            | PA66 PA66HIRHS                                                                           |
| UV Resistant (Yes/No)        | No                                                                                       |
| Operating Temperature        | -40°F to +221°F (-40°C to +105°C)                                                        |
| Reach Compliant (Article 33) | Yes                                                                                      |
| ROHS Compliant               | Yes                                                                                      |
| Package Quantity (Imperial)  | 2000                                                                                     |
| Package Quantity (Metric)    | 2000                                                                                     |
| Customs Number               | 3926909988                                                                               |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)