




## Technical Data

28.08.2023

Self-laminating labels, thermal transfer  
Helatag 1232

**TAG32-230TD1**

**Article Number 596-01903**



Material:	Type 1232, Polyester, white transparent, self-laminating (1232)
Colour:	White (WH), Transparent (CL)
Operating Temperature :	-40 °C to +150 °C
Curing Temperature:	from +2 °C
Bundle Ø min.:	30.24 mm
Bundle Diameter max (metric):	50.8 mm
Self adhesive (Yes/No):	Yes
Width (W):	32.00 mm
Height (H):	60.00 mm
Height (H2):	228.6 mm
Width of Liner (WL):	38.00 mm
Labels per Row:	1 pc.
Thickness of Foil:	50 µm
Adhesive:	Acrylic

We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved



## Technical Data

28.08.2023

Self-laminating labels, thermal transfer  
Helatag 1232

**Resistance to:**

Brake cleaner: 720h (at room temperature),  
Alcohol 94%: 720h (at room temperature),  
Hydraulic oil: 720h (at room temperature)

**Print Method:**

Thermal transfer print

**Application Tool:**

TT431, TT4030

**Recommended Ribbon Type:**

TT822OUT

**Application Method:**

The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.

