



TC6-T

Type T 6 ft Beaded Thermocouple Sensor

The Type T 6 ft Beaded Thermocouple probe includes 1.8m (6') of insulated 30-AWG wire wound on an integrated spool caddy /subminiature connector.



Key Advantages:

- 30-AWG wire
- Teflon-insulated probe

HOBO TC6-T Sensor Specifications

Range & Accuracy:

-200 to -65°C (-330° to -85°F) - $\pm 1.5\%$ accuracy \pm data logger accuracy

-65 to 130°C (-85° to 270°F) - $\pm 1.0^\circ\text{C}$ ($\pm 1.8^\circ\text{F}$) accuracy \pm data logger accuracy

130 to 180°C (270° to 356°F) - $\pm 0.75\%$ accuracy \pm data logger accuracy

Insulation: Type T Teflon®

*Note: Teflon insulation is rated up to 200°C (400°F) continuous, and +250°C (+482°F) for 24 hours.

**Note: Percentage is in degrees above or below ice point (0°C or 32°F)

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 6pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532