

Intelligent-WeighTM Hanging Scale



- Simple
- Digital Functionality
- Battery Operated
- Lightweight
- Easy to Use
- Hold Function









HS Series

A Higher Level of Precision . . . A Higher Level of Performance

Model	HS-7500	HS-15K	HS-30K
Capacity	7500 g / 16 lb	15 kg / 32 lb	30 kg / 66 lb
Readability	5 g / 0.01 lb / 0.2 oz	0.01 kg / 0.02 lb / 0.5 oz	0.02 lb / 0.05 lb / 1 oz
Divisions	1,500		
Weighing Units / Functions	g, lb, lb:oz		
Stabilization Time (seconds)	< 2		
Tare Range	To capacity by subtraction		
Safe overload	200% of rated capacity – ultimate overload 300%		
Power Source	4 size "C" type batteries (not included) or external power adapter (not included)		
Construction	ABS Plastic		
Display	1 in / 25.4 mm, 7 segment, wide viewing angle backlit LCD		
Pan Size (W x D)	Optional 12 inch diameter stainless steel hanging pan and cantilever beam		
Overall Dimensions (W x D x H)	4.72 x 2.25 x 7.25 in / 120 x 57 x 185 mm		
Operating Environment	32 °F to 104 °F non-condensing R.H. ≤ 85%		
Net Weight	1 lb / 1.5 kg		
Shipping Weight	2 lb / 0.9 kg		
Options	12 in diam. stainless steel hanging pan, AC/DC power adapter, Traveler™ transport case		

Features	Benefits	
Lightweight	Easy to use	
Large display	Can be easily read in less than ideal conditions	
Battery operation	Allows 250 hours of non-stop operation	
Automatic power save	Conserves battery power	
Hold function	Allows the last displayed weight to remain after the load is removed from the scale	
Auto Zero tracking	Ensures that you always start weighing at zero	