



Quality Products. Service Excellence.

## Type 4X Polyester Wallmount Enclosure *P JW Series*

Continuous Hinge Door with Twist Latches and 3 Pt Handle



**Panel  
Sold  
Separately**



### Application

- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

### Standards

- UL/cUL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- CSA Type 1, 2, 3, 4, 4X, 12 and 13
- Complies with
  - NEMA Type 1, 2, 3, 4, 4X, 12 and 13
  - IEC 60529, IP66

### Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Enhanced UV inhibitors protect against outdoor weathering.
- 3/8 collar studs are provided for optional inner panel mounting, hardware included. Note: Sizes 36x36" and larger have 8 collar studs for added stiffness.
- Stainless steel butterfly type "twist latch" door fasteners with padlock provision.
- Captive oil resistant gasket provides a positive seal.
- Integrated mounting flange.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
- Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in the Technical Information section.

### Finish

- Fiberglass polyester material has a gray finish.
- Optional inner panels are available in white powder coated finished steel.

### Accessories

- Additional Inner Panels
- Window Kits
- General Accessories
- Pole Mounting Kit
- Climate Control

**New and improved PDF part  
drawing files with more detail  
now available.**

Click part number in table below  
to access PDF, DXF, and STEP files.

Latch Part No.	3 Pt Handle Part No.	Enclosure			Optional Inner Panel		
		H	W	D	H	W	Part No.
PJEC363012T	PJEC3630123PT	36.48	30.50	12.18	33.00	27.00	<b>18P3327</b>
PJEC363012TW	PJEC3630123PTW	36.48	30.50	12.18	33.00	27.00	<b>18P3327</b>
PJW363014L	PJW363014L3PT	36.25	30.25	14.13	33.00	27.00	<b>18P3327</b>
PJW363610L	PJW363610L3PT	36.25	36.25	10.13	33.00	33.00	<b>18P3333</b>
PJW363614L	PJW363614L3PT	36.25	36.25	14.13	33.00	33.00	<b>18P3333</b>
PJW483610L	PJW483610L3PT	48.25	36.25	10.13	45.00	33.00	<b>18P4533</b>
PJW483614L	PJW483614L3PT	48.25	36.25	14.13	45.00	33.00	<b>18P4533</b>
PJW603610L	PJW603610L3PT	60.25	36.25	10.13	57.00	33.00	<b>18P5733</b>
PJW603614L	PJW603614L3PT	60.25	36.25	14.13	57.00	33.00	<b>18P5733</b>

Parts ending in W have window. Alternative inner panel options also available.

*Data subject to change without notice*

© 2022. Hammond Manufacturing Ltd. All rights reserved.