

Specification Sheet

Part Number: ATS10266210



Available in packages of 5,000 closures for high-volume applications.

Cable Tie Closures for ATS Systems, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel

Article Number	102-66210
Type	Closures_Black_ATS
Color	Black (BK)
Quantity Per	pack
Product Description	The cable tie closure for the ATS Flex is designed for optimized material utilization. This innovative two-piece system consists of a separate strap and closure, eliminating waste and the associated jobsite cleanup.
Short Description	Cable Tie Closures for ATS Systems, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel
Global Part Name	Closures_Black_ATS-PA66HSUV-BK

Minimum Tensile Strength (Imperial)	50
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	0.35
Length L (Metric)	9.0
Identification Plate Position	none
Reel Diameter (Imperial)	15.25
Reel Diameter (Metric)	387
Reel Width (Imperial)	3.5
Reel Width (Metric)	88.9
Releasable Closure	No
Variant	closures on reel
Width W (Imperial)	0.31
Width W (Metric)	8.0
Bundle Diameter Min (Metric)	0.0
Bundle Diameter Max (Imperial)	3.94
Bundle Diameter Max (Metric)	100

Height H (Imperial)	0.212
Height H (Metric)	5.4
Material	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
Material Shortcut	PA66HSUV
Flammability	UL 94 V-2
Halogen Free	Yes
UV Resistant (Yes/No)	Yes
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988
Reel Weight (Imperial)	3.5

Reel Weight (Metric)

1.58

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)