

## Specification Sheet

Part Number: T30R9PPC2



Polypropylene cable ties deliver excellent resistance to chemicals and salts.

Inside serrations provide strong grip on cables and wire bundles.

Easy application either manually or with a tensioning tool.

Bent tail ensures a quick and simple installation.

Cable Tie, 6" Long, 20lb Tensile Strength, PP, Natural, 100/pkg

Article Number 111-03017

Type T30R

Color Natural (NA)

Quantity Per pack

**Product Description** HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Cable Tie, 6" Long, 20lb Tensile Strength, PP, Natural, 100/pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T30R-PP-NA      |
| Minimum Tensile Strength (Imperial) | 20              |
| Minimum Tensile Strength (Metric)   | 89              |
| Length L (Imperial)                 | 5.83            |
| Length L (Metric)                   | 148.0           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.14            |
| Width W (Metric)                    | 3.6             |
| Bundle Diameter Min (Imperial)      | 0.31            |
| Bundle Diameter Min (Metric)        | 8.0             |
| Bundle Diameter Max (Imperial)      | 1.26            |
| Bundle Diameter Max (Metric)        | 32.0            |
| Thickness T (Imperial)              | 0.05            |

|                              |                                   |
|------------------------------|-----------------------------------|
| Thickness T (Metric)         | 1.2                               |
| Material                     | Polypropylene (PP)                |
| Material Shortcut            | PP                                |
| Flammability                 | UL 94 HB                          |
| Halogen Free                 | Yes                               |
| UV Resistant (Yes/No)        | No                                |
| Use Conditions               | For Indoor Use Only               |
| Operating Temperature        | -40°F to +239°F (-40°C to +115°C) |
| Reach Compliant (Article 33) | Yes                               |
| ROHS Compliant               | Yes                               |
| Package Quantity (Imperial)  | 100                               |
| Package Quantity (Metric)    | 100                               |
| Customs Number               | 3926909988                        |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Privacy Policy](#)

[Cookie Policy](#)

[Terms and Conditions](#)