

## Specification Sheet

Part Number: T40I0C2

Engineered and manufactured for maximum performance and quality.

Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.



Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 100/pkg

Article Number 111-04600

Type T40I

Color Black (BK)

Quantity Per pack

**Product Description** T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Cable Tie, 11" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 100/pkg

|                                     |                      |
|-------------------------------------|----------------------|
| Global Part Name                    | T40I-PA66-BK         |
| Minimum Tensile Strength (Imperial) | 40                   |
| Minimum Tensile Strength (Metric)   | 180                  |
| Length L (Imperial)                 | 11.61                |
| Length L (Metric)                   | 295.0                |
| Identification Plate Position       | none                 |
| Releasable Closure                  | No                   |
| Variant                             | Inside Serrated      |
| Width W (Imperial)                  | 0.16                 |
| Width W (Metric)                    | 4.0                  |
| Bundle Diameter Min (Imperial)      | 0.06                 |
| Bundle Diameter Min (Metric)        | 1.5                  |
| Bundle Diameter Max (Imperial)      | 3.15                 |
| Bundle Diameter Max (Metric)        | 80.0                 |
| Material                            | Polyamide 6.6 (PA66) |

|                               |                                  |
|-------------------------------|----------------------------------|
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Halogen Free                  | Yes                              |
| UV Resistant (Yes/No)         | No                               |
| Use Conditions                | For Indoor and Outdoor Use       |
| Plenum Rating                 | AH-2                             |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL 62275                         |
| UL Recognized (US)            | Yes                              |
| UL Listed (US and Canada)     | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| UL Listed (US)                | Yes                              |
| Package Quantity (Imperial)   | 100                              |
| Package Quantity (Metric)     | 100                              |

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)