

## Specification Sheet

Part Number: 111-15421

Engineered and manufactured for maximum performance and quality.

Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Complies with MS3367-6-2, Class 2 and SAE-AS33671.



Heavy Duty MilSpec Cable Tie, 32" Long, MS3367, 175lb Tensile Strength, PA66, Red, 25/bg

Article Number 111-15421

Type T150L

Color Red (RD)

Quantity Per pack

**Product Description** Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. Specially manufactured to comply with Military Specification MS3367-6-2, Class 2 and SAE-AS33671.

|                                     |  |
|-------------------------------------|--|
| Short Description                   | Heavy Duty MilSpec Cable Tie, 32" Long, MS3367, 175lb Tensile Strength, PA66, Red, 25/bg |
| Global Part Name                    | T150L-PA66-RD  |
| Minimum Tensile Strength (Imperial) | 175  |
| Minimum Tensile Strength (Metric)   | 780  |
| Length L (Imperial)                 | 32.3   |
| Length L (Metric)                   | 820.0  |
| Identification Plate Position       | none   |
| Releasable Closure                  | No   |
| Tie Closure                         | plastic pawl   |
| Variant                             | Inside Serrated  |
| Width W (Imperial)                  | 0.35   |
| Width W (Metric)                    | 8.9  |
| Bundle Diameter Min (Imperial)      | 0.31   |
| Bundle Diameter Min (Metric)        | 8.0  |
| Bundle Diameter Max (Imperial)      | 9.65   |
| Bundle Diameter Max (Metric)        | 245.0  |

|                                  |                                    |
|----------------------------------|------------------------------------|
| Thickness T (Imperial)           | 0.07                               |
| Thickness T (Metric)             | 1.9                                |
| Cable Tie Head Length (Imperial) | 0.51                               |
| Cable Tie Head Width (Imperial)  | 0.55                               |
| Height H (Imperial)              | 0.37                               |
| Height H (Metric)                | 9.5                                |
| Material                         | Polyamide 6.6 (PA66)               |
| Material Shortcut                | PA66                               |
| US MIL SPEC                      | MS3367-6-2, Class 2<br>SAE-AS33671 |
| Flammability                     | UL 94 V-2                          |
| Halogen Free                     | Yes                                |
| UV Resistant (Yes/No)            | No                                 |
| Use Conditions                   | For Indoor Use Only                |
| Plenum Rating                    | AH-2                               |
| Operating Temperature            | -40°F to +185°F (-40°C to +85°C)   |

|                               |            |
|-------------------------------|------------|
| Reach Compliant (Article 33)  | Yes        |
| ROHS Compliant                | Yes        |
| Certification/Specification   | UL 62275   |
| UL Recognized (US)            | Yes        |
| UL Listed (US and Canada)     | Yes        |
| UL Recognized (US and Canada) | Yes        |
| UL Listed (US)                | Yes        |
| Package Quantity (Imperial)   | 25         |
| Package Quantity (Metric)     | 25         |
| Customs Number                | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)