

Specification Sheet

Part Number: 120-06001

Independent tensioning drive provides unequalled tensioning control and repeatability.


New software and user interface make managing the bundling tension and speed, tracking performance, troubleshooting issues and logging data easier than ever before.

Counterbalanced hanger causes the AT2000 CPK to feel virtually weightless, enhancing ergonomics without restricting a user's motion.

Removable handle enables integration with fully automated applications to further increase productivity and decrease labor costs.

Configurable blade enables AT2000 CPK to cut cable ties flush or with a tail, depending on application requirements.

Complies with MS3367-4-9, Class 2 and SAE-AS33671.



MilSpec Cable Tie for AT2000, MS3367, 18lb Tensile Strength, PA66, Natural, 50/bandolier, 500/pkg

Article Number	120-06001
Type	T18RA50
Color	Natural (NA)
Quantity Per	pack

Product Description	The AT2000 CPK automatic cable tying system adapts to any industrial workflow. It excels in high-volume automatic bundling applications – especially where precision and repeatability are critical. The tool is electronically operated. Cycle rate is adjustable between 0.8 and 1.4 seconds, depending on what’s best for the application. With a pull of the trigger, the tool applies an 18 lb. cable tie around a wire or tube bundle and is instantly ready to apply the next. Cable ties are available on 50-piece bandoliers and 5,000-piece reels. The AT2000 CPK uses two discreet drive motors. One motor delivers the tie, the other controls tension. Tension consistency is monitored in the software – especially useful when verification is required. Configurable blade enables the AT2000 CPK to cut cable ties flush or with a tail, depending on application requirements. An onboard TFT display shows production data, fault diagnostics and device control in 19 languages. Accessories are available to enhance the tool's efficiency in various workflows from hand operated to fully automated. Specially manufactured to comply with Military Specification MS3367-4-9, Class 2 and SAE-AS33671.
Short Description	MilSpec Cable Tie for AT2000, MS3367, 18lb Tensile Strength, PA66, Natural, 50/bandolier, 500/pkg
Global Part Name	T18RA50-PA66-NA
Minimum Tensile Strength (Imperial)	18
Minimum Tensile Strength (Metric)	80
Length L (Metric)	152.4
Variant	bandolier
Width W (Imperial)	0.10
Width W (Metric)	2.5
Bundle Diameter Min (Imperial)	0.06

Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	0.79
Bundle Diameter Max (Metric)	20.0
Power supply unit	Electrical
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MIL SPEC	SAE-AS33671 MS3367-4-9, Class 2
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Use Conditions	For Indoor Use Only
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500

Customs Number

3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)