

Specification Sheet

Part Number: 126-00075



All-in-one bundling and mounting solution reduces costs.

Low-profile design provides dependable cable management in tight spaces.

1-Piece Cable Tie with Arrowhead Mount, 6"L, 50lb Tensile Strength, 5.4mm Round Hole, PA66HS, Black, 500/pkg

Article Number 126-00075

Type T50SOSKSFT5.4E

Color Black (BK)

Quantity Per pack

Product Description

The low-profile push mount design provides an overall shortened length, which assists in limiting protrusion on the opposing side of application surfaces. The mount's rounded tip allows for a smoother surface in case of contact with surrounding components or hands. The dome provides firm, rattle-free performance and keeps out debris. One-piece mounting ties offer a complete solution by both bundling and mounting.

Short Description

1-Piece Cable Tie with Arrowhead Mount, 6"L, 50lb Tensile Strength, 5.4mm Round Hole, PA66HS, Black, 500/pkg

Global Part Name T50SOSKSFT5.4E-PA66HS-BK

Minimum Tensile Strength (Imperial) 50

Minimum Tensile Strength (Metric) 180

Length L (Imperial) 6.0

Length L (Metric) 156.0

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.04

Bundle Diameter Min (Metric) 1.0

Bundle Diameter Max (Imperial) 1.38

Bundle Diameter Max (Metric) 35.0

| | |
|---|--|
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.05 |
| Panel Thickness Min (Metric) | 0.7 |
| Panel Thickness Max (Metric) | 1.3 |
| Mounting Hole Diameter D (Imperial) | 0.20 - 0.22 " |
| Mounting Hole Diameter D (Metric) | 5.2 - 5.6 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.20 |
| Mounting Hole Diameter D Max (Imperial) | 0.22 |
| Mounting Hole Diameter D Max (Metric) | 5.6 |
| Disc Diameter (Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HS |
| Flammability | UL 94 V-2 |
| UV Resistant (Yes/No) | No |

| | |
|------------------------------|-----------------------------------|
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)