

## Specification Sheet

Part Number: 126-00080

Design helps silence and stabilize the tie in high-vibration applications.

Arrowhead-style mount provides low insertion and high extraction force.



Anti-rotational oval fastener forces bundle to travel in intended direction.

Rubber seal restricts water and debris from passing through mounting hole.

1-Piece Cable Tie with Oval Arrowhead Mount with Seal, 6.2" Long, Mounting Hole Diameter 0.24 x 0.48", PA66HS, Black, 500/pkg

Article Number

126-00080

Type

T60SOSSFT62x122-E-MD

Color

Black (BK)

Quantity Per

pack

Product Description

Push Mount Ties with Seal for Oval Holes provide a one-piece bundling and mounting solution. The oval arrowhead fastener won't rotate once inserted into a panel hole, ensuring proper routing of wires and hoses. The welded rubber seal protects against the ingress of water and debris.

Short Description

1-Piece Cable Tie with Oval Arrowhead Mount with Seal, 6.2" Long, Mounting Hole Diameter 0.24 x 0.48", PA66HS, Black, 500/pkg

Global Part Name T60SOSSFT62x122-E-MD-PA66HS-BK

Minimum Tensile Strength (Imperial) 67

Minimum Tensile Strength (Metric) 300

Length L (Imperial) 6.2

Length L (Metric) 157.5

Fixation Method Arrowhead for oval holes

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.22

Width W (Metric) 5.5

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 1.18

Bundle Diameter Max (Metric) 30.0

Thickness T (Metric)	1.35
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.08
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	2.0
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 "
Mounting Hole Diameter D (Metric)	6.2 x 12.2 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.48
Mounting Hole Diameter D Max (Metric)	12.2
Disc Diameter (Metric)	16.0 x 22.0
Disc Diameter (Imperial)	0.63 x 0.87
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2

UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Privacy Policy](#)   [Cookie Policy](#)   [Terms and Conditions](#)