

Specification Sheet

Part Number: 133-04043

Secures two routings together while keeping them separated, to prevent chafing or heat transfer.

Inverted retaining legs and narrow opening prevent inadvertent disengagement.

Controlled flex and angled entry promote easy installation.

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in an 8mm hole.



Tube and Pipe Clip with 8mm Fir Tree, 2x 6.5-7.0mm Diameter, PA66HIRHS, Black, 3000/ctn

Article Number 133-04043

Type PC6.5x2FT8.0

Color Black (BK)

Quantity Per pack

Product Description This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.

Short Description Tube and Pipe Clip with 8mm Fir Tree, 2x 6.5-7.0mm Diameter, PA66HIRHS, Black, 3000/ctn

Global Part Name PC6.5x2FT8.0-PA66HIRHS-BK

Length L (Imperial)	1.17
Length L (Metric)	29.6
Fixation Method	Fir Tree
Width W (Imperial)	0.39
Width W (Metric)	10.0
Bundle Diameter Min (Imperial)	0.26
Bundle Diameter Min (Metric)	6.5
Bundle Diameter Max (Imperial)	0.28
Bundle Diameter Max (Metric)	7.0
Height H (Imperial)	1.06
Height H (Metric)	26.9
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.22
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	5.5
Mounting Hole Diameter D (Imperial)	0.31 "

Mounting Hole Diameter D (Metric)	8.0 mm
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)