

Specification Sheet

Part Number: 133-04044

Secures two routings together while keeping them separated, to prevent chafing or heat transfer

Inverted retaining legs and narrow opening prevent inadvertent disengagement

Controlled flex and angled entry promote easy installation

Robust arrowhead design provides low insertion effort yet delivers exceptional retention strength in a 65 mm hole

For use with routings of the following size: 2x 47-51mm



Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Article Number 133-04044

Type PC5X2SO

Color Black (BK)

Quantity Per pack

Product Description This clip features a modular design that can be used individually or lined together to secure multiple pipes or hoses.

Short Description Tube and Pipe Clip with 6.5mm Arrowhead, 1.2-1.6mm Panel Thickness, PA66HIRHS, Black, 5000/ctn

Global Part Name PC5X2SO-PA66HIRHS-BK

Length L (Imperial)	0.97
Length L (Metric)	23.74
Fixation Method	Arrowhead
Width W (Imperial)	0.88
Width W (Metric)	22.35
Height H (Imperial)	1.14
Height H (Metric)	28.9
Panel Thickness Min (Imperial)	0.02
Panel Thickness Max (Imperial)	0.04
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	1.0
Mounting Hole Diameter D (Imperial)	0.24 x 0.27 "
Mounting Hole Diameter D (Metric)	6.1 - 6.9 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.27

Mounting Hole Diameter D Max (Metric)	6.9
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5008
Package Quantity (Metric)	5000
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)