

Specification Sheet

Part Number: 150-52693



Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

Initial fir tree serves as a locating feature for assistance in blind assembly applications.

Disc feature provides anti-rattle protection in high vibration applications.

2-Piece Cable Tie with Fir Tree Mount, 6.0" Long, 0.25 - 0.28" Mounting Hole, PA66HS, Black, 500/pkg

Article Number 150-52693

Type T50SOSFT6SD

Color Black (BK)

Quantity Per pack

Product Description Fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie.

Short Description 2-Piece Cable Tie with Fir Tree Mount, 6.0" Long, 0.25 - 0.28" Mounting Hole, PA66HS, Black, 500/pkg

Global Part Name T50SOSFT6SD-PA66HS/PA66HIRHS-BK

| | |
|-------------------------------------|--------------------------|
| Minimum Tensile Strength (Imperial) | 50 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 150 |
| Fixation Method | Fir tree for round holes |
| Identification Plate Position | none |
| Tie Closure | plastic pawl |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.04 |
| Bundle Diameter Min (Metric) | 1.0 |
| Bundle Diameter Max (Imperial) | 1.22 |
| Bundle Diameter Max (Metric) | 31.0 |
| Height H (Imperial) | 0.05 |
| Height H (Metric) | 1.3 |

| | |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------|
| Panel Thickness Min (Imperial) | 0.03 |
| Panel Thickness Max (Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 0.75 |
| Panel Thickness Max (Metric) | 3.0 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.28 " |
| Mounting Hole Diameter D (Metric) | 6.4 - 7.1 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.28 |
| Mounting Hole Diameter D Max (Metric) | 7.1 |
| Disc Diameter (Metric) | 16.0 |
| Disc Diameter (Imperial) | 0.63 |
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Foot Part Material | PA66HIRHS |
| Material Shortcut | PA66HS PA66HIRHS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |

| | |
|------------------------------|-----------------------------------|
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor and Outdoor Use |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)