

## Specification Sheet

Part Number: 151-00378



Clips can be connected to each other to create a chain of cable harnesses.

Secures firmly to surfaces to eliminate moisture and corrosion.

Quick and easy installation ideal for the production environment.

Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg

Article Number 151-00378

Type IAHC3AH

Color Black (BK)

Quantity Per pack

Product Description Automatic Harness Clips offer a simple and secure method of attaching cables to panels and other surfaces. When the cable is pushed inside, it automatically activates the locking features which causes it to close. These are also connectable which allows for multiple cables to be positioned next to each other. These come in various sizes to fit different bundle diameters.

Short Description Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg

Global Part Name

IAHC3AH-PA66HIRHS-BK

Length L (Imperial)

1.6

Length L (Metric)

40.0

Fixation Method

Fir Tree

Width W (Imperial)

0.4

Width W (Metric)

13.5

Bundle Diameter Min (Imperial)

0.75

Bundle Diameter Min (Metric)

19.0

Bundle Diameter Max (Imperial)

1.1

Bundle Diameter Max (Metric)

28.0

Height H (Imperial)

2.5

Height H (Metric)

64.5

Panel Thickness Min (Imperial)

0.03

Panel Thickness Max (Imperial)

0.11

Panel Thickness Min (Metric)

0.5

Panel Thickness Max (Metric)

2.7

|   |  |
|---|--|
| Mounting Hole Diameter D (Imperial)     | 0.24 - 0.26 "  |
| Mounting Hole Diameter D (Metric)       | 6.2 - 6.7 mm   |
| Mounting Hole Diameter D Min (Imperial) | 0.24   |
| Mounting Hole Diameter D Max (Imperial) | 0.26   |
| Mounting Hole Diameter D Max (Metric)   | 6.7  |
| Disc Diameter (Metric)                  | 24.0   |
| Disc Diameter (Imperial)                | 0.94   |
| Material                                | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) |
| Material Shortcut                       | PA66HIRHS  |
| Flammability                            | UL 94 HB   |
| UV Resistant (Yes/No)                   | No   |
| Use Conditions                          | For Indoor and Outdoor Use                                       |
| Operating Temperature                   | -40°F to +221°F (-40°C to +105°C)                                |
| Reach Compliant (Article 33)            | Yes  |
| ROHS Compliant                          | Yes  |

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 500        |
| Package Quantity (Metric)   | 500        |
| Customs Number              | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2026 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Privacy Policy](#) [Cookie Policy](#) [Terms and Conditions](#)